STRICTS.

STRICT TO A SATISFACTORY PROJECT AND THE CT OR STRUCTURAL STATE ARCHITECT. Y+3 # 1
R STD. & BET.
ICT WITH
PRESSURE TREATED
PECE SHALL
I,D.F.#2 ABOVE GROUN TED TO MATCH 10N 2231.A.5 CONCRETE MORTAR AND RELATED MATERIALS TO NFORM TO APPLICABLE PROVISIONS OF TITLE 24 CEPT AS MODIFED HEREIN.

REINFORCEING BARS:ASTM A615 OR ASTM A708 FORMED GRADE 40 BILLET STEEL.

EXPANSION JOINT FILLER: ASTM D994
FORM MATERIALS: SIDE FORMS DOUGLAS FIR.

NISTRUCTION GRADE OR BETTER: OR METAL

NEMS. CLIMICNI, PLACING CONCRETE URING AND REMOVAL OF ACCORDANCE WITH APPLICABLE 24, PART 2. HANE, MANUFACTURED BY MAMECO "GEOCEL" SILICONIZED CAULK, GE, P FOR ALL OTHER APPLICATIONS. O ible doors shall be 3 se door position of 3" from WITH 1.25 TO ASTM ON THE ont Entity Evolution of STEEL GENERAL ANNOTHME

OSED SJRFACES SHALL BE PAINTED LOCAL

AND THRESHOLDS. MATERIAL SHALL BE OF THE GRADE

ED OR EQUAL.

R - WOOD SIDING, TRIM AND SKIRTING FLAT OR SEMI-GLOSS

R - WOOD SIDING, TRIM AND SKIRTING FLAT OR SEMI-GLOSS

R - WOOD SIDING, TRIM AND SKIRTING FLAT OR SEMI-GLOSS

R - WOOD SIDING, TRIM AND SKIRTING FLAT OR SEMI-GLOSS

R - WOOD SIDING, TRIM AND SKIRTING FLAT ONE FINISH

COAT OF THE INSPECTOR, AND AT LEAST ONE FINISH

PRIME COAT SHALL BE APPLIED

ACTURER'S RECOMMENDATION. PRIME AND FINISH COATS SHALL

MPATIBLE AND MANUFACTURED BY THE SAME COMPANY.

R TRIM. - TRIM NOT PRECOATED SHALL BE PAINTED WITH TWO

R TRIM. - TRIM NOT PRECOATED SHALL BE PAINTED WITH TWO NOTES AND AS DETERMINED BY THE SCHOOL
THE CONTRACTOR SHALL PLACE WOOD
SUITABLE SUPPORTS AS DETAILED ON THE SPE PAINTED WITH TWO COATS ED PROFILES BY FORMING RAIGHT, SHARD? FIT NERS, HAIRLINE JOINTS IXLE OR OTHER DEFECTS EANED THOUROUGHLY,ALL COAT. SURFACING AS MANUFACTURED ARABLE. (0.7 MIN. C.O.F.)
L BE LISTED ON THE
S LIST FOR MAINTENANCE
. OR EQIAL. E SITE ON WHEEL ASSEMBLY E. GREAT CARE SHALL BE TS BY RACKING OR BUMPING EXCEPT ALUMINUM WINDOW BE OF THE GRADE CIFICATIONS COORDINATION OF WORK

IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO MAKE ALL

IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO MAKE ALL

IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO MAKE ALL

IN SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO MAKE ALL

IN SCENEY ARRANGEMENTS WITH THE SCHOOL DISTRICT AUTHORIZED

REPRESENTATIVE FOR ACCESS TO GROUNDS AND REMOVAL OF

EQUIPMENT, IF NECESSARY.

THIS CONTRACT SHALL BE MADE AT LEAST 48 HOURS PRIOR TO

DELIVERY OF AY MODULE.

ON-SITE INSPECTION SHALL BE DONE BY THE SITE INSPECTOR.

THE SITE SHALL BE MANUFACTURER OR HIS SUBCONTRACTORS PERFORM AT

INFERIOR HEIGHT, LOOR TO CEILING SHALL BE 8'-6' U.O.N.

THE SITE SHALL BE SUBJECT TO THE INSPECTION OF THE SITE INSPECTOR

WITH SUCH INFORMATION AS MAY BE NECESSARY TO KEEP HIM FULLY

INFORMED AS TO PROGRESS OF WORK AND DATES WHEN SITE WORK

WILL OCCUR. THE CONTRACTOR SHALL NOTIFY THE INSPECTION

AGENCY AT LEAST 48 HOURS PRIOR TO THE INSPECTION

ACENCY AT LEAST 48 HOURS PRIOR TO THE DELIVERY OF

ANY CLASSROOM(S) BY VISTING EACH SITE (THIS MAY BE DONGENTHATION SHALL PREVAIL.

BY THE INSPECTIONS.

CONTRACT SHALL BE SCHOOL DISTRICT BETWEEN HIM BUILDING COCCUPIES.

CALCULATION OF THE SQUARE FOOTAGE THE BUILDING OCCUPIES.

CALCULATION OF THE SALL HAVE A MINIMUM 2' OVERHANGS. FULL LEAST AND DAWNSPOUTS SHALL HAVE A MINIMUM ROOF OVERHANGS.

THE ENTRACEE WALL SHALL HAVE A MINIMUM CO' OVERHANG.

FULL ERROR WALL SHALL HAVE A MINIMUM ROOF OVERHANG.

THE ENTRACE WALL SHALL HAVE A MINIMUM ROOF OVERHANG.

THE ENTRACE WALL SHALL HAVE A MINIMUM ROOF OVERHANG.

THE ENTRACE WALL SHALL HAVE A MINIMUM ROOF OVERHANG.

THE ENTRACE WALL SHALL HAVE A MINIMUM ROOF OVERHANG.

THE ENTRACE WALL SHALL HAVE A MINIMUM ROOF OVERHANG.

THE ENTRACE WALL SHALL HAVE A MINIMUM ROOF OVERHANG.

THE ENTRACE WALL SHALL HAVE A MINIMUM ROOF OVERHA #14.

RECEPTACLES - AS NOTED. +18" A.F.F. MIN.

CLOCK RECEPTACLE - AS NOTED.

SWITCHES - AS NOTED. +48" A.F.F. MAX.

LIGHTING FIXTURES - AS NOTED ON THE DRAWINGS.

WORKMANSHIP

MATERIALS AND EQUIPMENT INSTALLED IN A SECURE, NEAT

WORKMANLIKE MANNER IN ACCORDANCE WITH CODE REQUIREMENTS.

PANELBOARD CARDS FILLED OUT. CONDUIT AND CABLE INSTALLED IN

WALL AND CEILING SPACES. WORK PIERCING WATERPROOFED AREAS

FLASHED AND SEALED TO A WATERTIGHT CONDITION.

BUILDING CONDUIT/WIRING FROM FACE OF BLDG TO SITE TERMINATION

BY SITE CONTRACTOR(N.I.C.). (FLEXIBLE CONDUIT S-BEND SEALTITE) NEW COMPLYING WITH REQUIREMENTS OF CALIFORNIA ELECTRICAL NEW COMPLYING WITH REQUIREMENTS OF CALIFORNIA ELECTRICAL DE AND NATIONAL FIRE PROTECTION ASSOCIATION
DE AND NATIONAL FIRE PROTECTION ASSOCIATION
TRIC METALLIC TUBING - COUPLING AND FLEX CONDUIT
VANIZED OR SHERARDIZED. EXTERIOR FLEX- GALV. STEEL
FACTORY APPLIED P.V.C., JACKET,
ELBOARDS - FLUSH MOUNTED.
ELBOARDS - COPPER, INSULATED FOR 600 VOLTS. TYPE THHN FOR ES #12 TO #6, TYPE THW FOR LARGER SIZES, MINIMUM SIZE-OF WORK

COTOR SHALL PROVIDE ALL LABOR, MATERIALS AND SERVICES

ECTRICAL INSTALLATION COMPLETE WITH ASSOCIATED

EENT AND FIXTURES, IN OPERATING CONDITION READY FOR
THE WORK INCLUDES: LIGHT AND POWER SYSTEMS, LIGHTING
ES COMPLETE WITH LAMPS, CONNECTIONS AND DISCONNECTS TO
DUIPMENT. APPOS 1111195 CO 111193 WORKMANSHIP SHALL BE EQUAL OR BETTER IN QUALITY TO THAT REQUIRED BY THE CONSTRUCTION TRADES FOR A FINISHED PRODUCT. A QUALITY CONTROL SUPERVISOR, DESIGNATED BY THE MANUFACTURER, SHALL REVIEW ALL WORK IN PROGRESS AND SHALL REVIEW THE FINISHED BUILDING PRIOR TO FINAL INSPECTION TO ASSURE IT IS COMPLETE AND CORRECT. THE QUALITY CONTROL SUPERVISOR SHALL HAVE THE AUTHORITY TO HAVE MATERIALS REPLACED AND WORK REDONE IN ORDER TO CORRECT FAULTY MATERIALS OR WORKMANSHIP. STAMPED NOT ENGRAVED) METAL IDENT (STAMPED NOT ENGRAVED) METAL IDENT DIMENSIONS
THE BUILDINGS SHALL OCCUPY AN AREA OF 960 SOUARE FEET WITH TOLERANCE OF MINUS 5 SOUARE FEET. THE BUILDINGS SHALL BE 24' X 40'. ALL BUILDINGS SHALL MEET THE SQUARE FOOTAGE REQUIREMENT. LINEAR DIMENSIONS SHALL BE VERTICAL TRIM FINISH LINE TO VERTICAL TRIM FINISH LINE. FINISH AND BASE MATERIALS AT EACH MODULE SHALL TERMINATE AT INTERIOR MODULE JOINTS IN A MANNER TO JOIN FLUSH AND TIGHT WITH SAME MATERIAL IN ADJACENT MODULE SO THE MODULE MAY BERELOCATED WITH MINIMUM CUTTING AND PATCHING. ENERAL DESIGN REQUIREMENTS:

WO (2) APPROXIMATELY 12' X 40' MODULES DESIGNED SO THAT TWO ODULES MAY BE JOINED TOGETHER TO FORM A COMPLETE STRUCTURE ) MAINTAIN A POSITIVE ALIGNMENT OF FLOORS, WALLS, AND ROOF ND TO PERMIT SIMPLE NON-DESTRUCTIVE DETACHMENT FOR FUTURE ELOCATION. IDENTIFIED WITH AN IMPRINTED IFFICATION TAG 3"X1 -1/2". ORMATION: PC 02-104915 7 Z