



STUD WALL INTERSECTIONS AND CORNERS
NOTE: SEE SHEET S-10 FOR DETAILS OF SQUARE COLUMNS IN STUD WALLS.

GENERAL NOTES
1. FOUNDATION MATERIAL IS COMPACT SAND MAXIMUM SOIL PRESSURE UNDER FOOTINGS IS 1800 P.S.F. D.L. + L.L. 1000 P.S.F. D.L. ONLY.
2. ELEVATION OF BOTTOM OF FOOTING AS NOTED ON FOUNDATION PLAN.
3. FOOTINGS SHALL EXTEND 12\"/>

FOUNDATION
1. FOUNDATION MATERIAL IS COMPACT SAND MAXIMUM SOIL PRESSURE UNDER FOOTINGS IS 1800 P.S.F. D.L. + L.L. 1000 P.S.F. D.L. ONLY.
2. ELEVATION OF BOTTOM OF FOOTING AS NOTED ON FOUNDATION PLAN.
3. FOOTINGS SHALL EXTEND 12\"/>

CONCRETE
1. CONCRETE IS 3000 P.S.I., AT 28 DAYS.
2. SEE SPECIFICATIONS FOR TREATMENT OF SURFACES OF HORIZONTAL AND VERTICAL JOINTS.
3. ALL ANCHOR BOLTS, STRAP ANCHORS, DOWELS, REINFORCING BARS, ETC. SHALL BE SET AND SECURELY FASTENED BEFORE CONCRETE IS Poured.
4. UNLESS NOTED OTHERWISE CONCRETE COVERAGE FOR REINFORCING BARS SHALL BE AS FOLLOWS:
5. WHERE CONCRETE IS EXPOSED TO EARTH BUT PLACED IN FORMS, 1/2\"/>

MINIMUM NAILING SCHEDULE
ALL NAILS SHALL BE COMMON WIRE NAILS. WHERE NAILING TENDS TO SPLIT THE WOOD, NAILS SHALL BE SHARP DRILLED.
BUILT-UP BEAMS, 10\"/>

WOOD FRAMING
1. ALL LUMBER SHALL BE GRADE MARKED DOUGLAS FIR. SEE SPECIFICATIONS FOR GRADES.
2. WOOD PLATES AND SILL PLATES SHALL HAVE 1\"/>

| WASHER SCHEDULE | | | MALL IRON | | |
|-----------------|-------|-----------------|-----------|-----------------|-----------------|
| BOLT SIZE | STEEL | SCHEDULE | STEEL | SCHEDULE | MALL IRON |
| 1/2" | ROUND | 2 1/2" x 1 1/4" | ROUND | 2 1/2" x 1 1/4" | 2 1/2" x 1 1/4" |
| 3/4" | ROUND | 2 1/2" x 1 3/4" | ROUND | 2 1/2" x 1 3/4" | 2 1/2" x 1 3/4" |
| 3/4" | ROUND | 2 1/2" x 1 1/2" | ROUND | 2 1/2" x 1 1/2" | 2 1/2" x 1 1/2" |
| 3/4" | ROUND | 2 1/2" x 1 3/8" | ROUND | 2 1/2" x 1 3/8" | 2 1/2" x 1 3/8" |
| 1" | ROUND | 3 1/4" x 3/8" | ROUND | 3 1/4" x 3/8" | 3 1/4" x 3/8" |

LEGEND
ELEV. BOTTOM OF FTG.
S STEP IN FTG.
ELEV. BOTTOM OF ARCHIVE S.E.C. 7
ELEV. EXPANSION JOINT
ELEV. TOOLED JOINT
CONSTRUCTION JOINT
DETAIL DESIGNATION
CONCRETE IN SECTION
TRIP-L-GRIP TYPE 'C' WITH STANDARD TRIP-L-GRIP
SHARPER MTL. EACH NOTE.
LEGEND
CONCRETE IN SECTION
TRIP-L-GRIP TYPE 'C' WITH STANDARD TRIP-L-GRIP
SHARPER MTL. EACH NOTE.

STATE OF CALIFORNIA
DEPT. OF PUBLIC WORKS
DIVISION OF ARCHITECTURE
WILLIAM T. WHEELER
STRUCTURAL ENGINEER
11314 APPROVED
APR. 10, 1953
105 ANGELS, CALIFORNIA

MEM. CO. SUPERINTENDENT OF SCHOOLS
APPROVED
DATE 10-29-53

BAKERSFIELD CITY SCHOOL DISTRICT
BOARD OF EDUCATION
APPROVED
DATE 10-29-53

REVISIONS
DATE

DRAWN BY
CHECKED BY
JOB NO.
ARCHITECT
C-695

ROBERT A. N. EDDY
ARCHITECT A.I.A.
2901 H ST. BAKERSFIELD, CALIFORNIA PH. 59048

GENERAL NOTES AND TYPICAL DETAILS
LINCORN JUNIOR HIGH SCHOOL
BAKERSFIELD
MEM. COUNTY, CALIFORNIA