



21 TYPICAL CHAIN LINK FENCE AND GATES

A1.05 ADY100-02

TYPICAL FENCE & GATE KEYNOTES

- | | |
|---|---|
| <p>① 4" O.D. (6"Ø FOR 8' HIGH FENCE W/ 10' WIDE GATE) GALVANIZED STEEL GATE POST (9.1 lb/ft)</p> <p>② 2 7/8" O.D. GALVANIZED STEEL END OR CORNER POST (5.79 lb/ft)</p> <p>③ 2" O.D. GALVANIZED STEEL GATE FRAME (2.72 lb/ft)</p> <p>④ 1 5/8" O.D. GALVANIZED STEEL HORIZONTAL RAIL (2.27 lb/ft)</p> <p>⑤ 2"x2" MESH x 9 GAUGE GALVANIZED FENCE FABRIC WITH KNUCKLED TOP AND BOTTOM SELVAGE. FENCE FABRIC TO BE GALVANIZED BEFORE WEAVING (GBW)</p> <p>⑥ 1/4"x3/4" GALVANIZED STEEL STRETCHER BAR</p> <p>⑦ GALVANIZED STEEL STRETCHER BAR TENSION BAND, MIN. OF 6 TENSION BANDS</p> <p>⑧ ENTRY ACCESSIBILITY SIGN FOR ACCESSIBLE GATE PER DETAIL 2
A-801</p> <p>⑨ GALVANIZED ADJUSTABLE TURNBUCKLE FOR 3/8" DIA. TRUSS ROD</p> <p>⑩ 3/8" DIA. GALVANIZED STEEL ADJUSTABLE TRUSS ROD. TRUSS RODS REQUIRED FOR ALL GATE POST PANELS AND END OR CORNER POST PANELS</p> | <p>⑪ 3/8"x6" GALVANIZED HOOK BOLT WITH NUT IMBEDDED IN MIDWAY BETWEEN POSTS</p> <p>⑫ 7 GAUGE (0.177" DIA.) GALVANIZED STEEL TENSION WIRE</p> <p>⑬ RAINPROOF CAP</p> <p>⑭ LOCKING HASP</p> <p>⑮ 180° GATE HINGE, TYP</p> <p>⑯ 12"Ø CONCRETE POST FOOTING (TYP.)</p> <p>⑰ TRIM, LEVER HANDLE & RIM CYLINDER LOCK PER DISTRICT STANDARD - 5LB MAX OPERATING FORCE, MOUNTED AT +34" - 44"</p> <p>⑱ 16ga GATE GUARD</p> <p>⑲ 10" HIGH x GATE WIDTH, 16 ga POWDER-COATED METAL KICK PLATE, TYP BOTH SIDES OF GATE.</p> <p>⑳ GALVANIZED STEEL PIPE SLEEVE FOR GATE DROP ROD</p> <p>㉑ PROVIDE SERIES 3200 KNOX BOX @ ALL ENTRY GATES REQ'D FOR FIRE DEPARTMENT ACCESS. SEE SITE PLAN</p> <p>㉒ MOW STRIP - SEE 8/A1.03</p> |
|---|---|

SCALE: N.T.S.