YPICAL VENT: 1/4" CORROSION RESISTANT MESH.

PREFORMED L- SIZE REQUIRED WITH 3" RETURN.

AREA: 960 S.F./150= 6.4 S.F. RQD

4- 3"x48" SIDE WALL VENTS= 4.0 S.F 5- 3"x24" END WALL VENTS = 2.5 S.F.

(1A)(5)

16

WHEN FND HEIGHT EXCEEDS 6" USE

15.-1 1/8.

1/4'=1'-0"

50+20-PSF

0 0

24'-2 1/4"- FOUNDATION

23'-11"- BLDG. ENDWALLS

12'-1 1/8"

TYPICAL 24×40 FOUNDATION PLAN

3"x48" SIDE VENT = 1.00 S.F. 3"x21" END VENT = .5 S.F.

BUILDING VENTILATION

3"×24" END WALL VENTS

BUILDING APPLICATIONS

MIN.18" FROM MODLINES

OPTIONAL 4" SEPARATION

AS REQUIRED FOR ADJACENT

MIN.18" FROM BLDG. CORNER

MIN.12" BLOCKING BETWEEN VENTS

4" SEPARATION

FOUNDATION PADS AT

ADJACENT BUILDINGS

1/4'=1'-0"

TIE PLATES:

6 EA. 6 EA. (24)

WHEN FND HEIGHT

EXCEEDS 6" USE

REVISIONS BY

CL SSING LC

s Leasing, LLC

CLASS LEASING, INC.
STOCKPILE CLASSROOM
24x40 - 50+20 PSF RELOCATION
FOUNDATION PLAN & DETAILS

DATE 09-29-2014
SCALE
DRAWN LAM-CLLS

24x40 50+20 PSF SHEET **F2.1**

RELOCATION FOUNDATION PLAN & DETAILS