




TYP FLOOR JOIST COPING



1 TYP JOIST ATTACHMENT TO BEAM  
S2 1 1/2"=1'-0"



3 TYP. BEAM TO BEAM CONNECTION  
S2 1 1/2"=1'-0"



14 GA. JOIST

12 GA. JOIST


Z SECTION PROPERTIES

A=0.89 IN.<sup>2</sup>  
S<sub>x</sub>=1.85 IN.<sup>3</sup>  
I<sub>x</sub>=6.37 IN.<sup>4</sup>

Z SECTION PROPERTIES


A=1.38 IN.<sup>2</sup>  
S<sub>x</sub>=2.97 IN.<sup>3</sup>  
I<sub>x</sub>=10.20 IN.<sup>4</sup>

1A TYP JOISTS  
S2 1 1/2"=1'-0"




4 TYP. ANGLE TO Z-PURLIN ATTACHMENT  
S2 1 1/2"=1'-0"

NOTE:  
AT 48'x40' BUILDINGS THE  
TIE PLATES AT AT COLUMN END  
CAN NOT BE REPLACED BY  
THE ALTERNATE BOLT ON WOOD  
FOUNDATIONS.



2 TYP. FL. BEAM CONNECTION  
S2 1 1/2"=1'-0"



A TYPICAL FLOOR FRAMING LAYOUT  
S2 1 1/2"=1'-0" PLYWOOD FLOOR

- KEY NOTES -

- 1 C 7x9.8 FLOOR BEAM  
ALTERNATE C10x15.3
  - 2 HSS COLUMN PER SHEET S4
  - 3 FLOOR JOIST (SEE 1A/S2)
- | FLOOR JOIST SCHEDULE |              |              |
|----------------------|--------------|--------------|
| SPACING              |              |              |
| LIVE LOAD PSF        | 14 GA. JOIST | 12 GA. JOIST |
| 50 PSF               | 48" O.C.     | 48" O.C.     |
| 50+15 PSF            | 24" O.C.     | 48" O.C.     |
| 100 PSF              | 24" O.C.     | 24" O.C.     |
| 150 PSF              |              | 24" O.C.     |
- 4 1 1/8" T&G PLYWOOD FLOOR SHIT'G  
STURDI-I-FLOOR 48" O.C SPAN RATING EXP. 1  
COMFORMING TO PS 1-95  
OPTION: UNI-FLOOR BY PITTSBURGH  
TESTING LAB CONFORMING TO PS 1-95.  
STAGGER SHEETS 48" O.C AS SHOWN W/  
FACE GRAIN NORMAL TO FLOOR JOISTS.  
FASTENING: BOUNDARY OF EA. MODULE:  
#12x2 1/4" WOOD TEK @ CHANNEL @ 6" O.C  
PANEL EDGES: ET&F 0.144"x2" MIN.  
POWER DRIVEN PINS @ 8" O.C.  
FIELD: ET&F 0.144"x2" MIN. POWER  
DRIVEN PINS @ 10" O.C.  
NOTE: SEE ICC ER-4144 FOR ET&F  
BRAND PNEUMATIC PINS.
  - 5 PLATE 1/8"x 3 1/2"x6"  
W/(8)#12x1" SHEET METAL SCREWS  
@ 10'-0" O.C MAX  
  
ALTERNATE:  
1/2"x1 1/2" MB @ 10'-0" O.C TYP  
(8'-0" O.C. MAX @ 48"x40' 150 PSF FLOOR  
LIVE LOAD BUILDING ON WOOD FOUNDATIONS)  
MAX AND 6" MAX FROM EACH END OF MOUDLE.  
BOLT @ + 1/8" MAX HOLE THRU CHANNELS
  - 6 3"x3"x14 GA. ANGLE @ UNSUPPORTED PLYWOOD  
EDGES @ THE TWO END MODULES OF 48'x40'  
150 P.S.F BUILDING ON WOOD FOUNDATION ONLY.  
PER DETAIL 4/S2

- GENERAL NOTES -

1. THE MATERIAL THICKNESS OF STRUCTURAL MEMBER,  
IN THEIR END-USE, SHALL MEET OR EXCEED THE  
MINIMUM BASE METAL THICKNESS SPECIFIED IN THE  
TABLE OR IN THE PLAN. THE MATERIAL GAUGE  
DESIGNATION IN THE PLAN SHALL BE USED AS  
REFERENCE ONLY.

- MODULE SCHEDULE -

BLDG SIZE (FT)	TOTAL # OF 12' WIDE MODULES	"A" TOTAL # OF CENTER MODULES	"B" TOTAL BLDG WIDTH
24' x 40'	2	0	23'-8 1/4"
36' x 40'	3	1	36'-6 1/2"
48' x 40'	4	2	47'-4 3/4"
60' x 40'	5	3	59'-3"
72' x 40'	6	4	71'-1 1/4"
84' x 40'	7	5	82'-11 1/2"
96' x 40'	8	6	94'-9 3/4"
108' x 40'	9	7	106'-8"
120' x 40'	10	8	118'-6 1/4"

REVISIONS		
NO	DATE	DESCRIPTION

DATE: 02/11/08  
SCALE: NOTED  
DRAWN BY: DM  
SERIAL NO.:

CUSTOMER:  
2:12 PITCHED ROOF 24' x 40' THRU 120' x 40' RELOCATABLE BUILDINGS  
FLOOR FRAMING PLANS (PLYWOOD)

**AMS**  
American Modular Systems Inc.  
787 Sprickels Ave, Manteca, CA 95336  
(209)825-1921 Fax: (209)825-7018  
americanmodular.com

APPROVALS:  
THESE DRAWINGS ARE PRELIMINARY  
AND NOT FOR CONSTRUCTION UNLESS  
STAMPED & SIGNED BY THE ENGINEER  
OF RECORD.

REGISTERED PROFESSIONAL ENGINEER  
Kenneth A. Luttrell  
No. 1418  
EXP. 3-31-09  
Structural Engineer  
STATE OF CALIFORNIA

IDENTIFICATION STAMP  
DIV. OF THE STATE ARCHITECT  
112985  
AC FLS SS  
DATE: 02/21/2008

IDENTIFICATION STAMP  
DIV. OF THE STATE ARCHITECT  
OFFICE OF REGULATION SERVICES  
PC 02-109695  
AC FLS SS  
DATE: 3/22/2009

PROJECT No.  
PC  
**S2**

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF AMERICAN MODULAR SYSTEMS AND ARE NOT TO BE REPRODUCED, COPIED OR CURED IN ANY FORM OR MANNER, NOR ARE THEY TO BE ASSIGNED TO ANY THIRD PARTY WITHOUT THE WRITTEN AUTHORIZATION OF AMERICAN MODULAR SYSTEMS.