



- FLOOR PLAN NOTES**
- Patch walls as required.
 - Match (E) finish - paint.
 - Match (E) ceramic tile.
 - REMOVE VENTS IN WALL. FILL W/CAAT 18 G.C. 4" x 8" TOE N. EA. END 3/4" RADIUS ADJACENT WALL - PAINT (N) MATCH.
 - Asphalt tile and (N).
 - Patch (E) floor as required. Match (E) finish, accessible threshold.
 - Replace (E) sink and counter-top with (N) sink counter-top as patch.
 - Remove (E) toilet.
 - Remove (E) toilet dispenser.
 - (N) paper towel dispenser.
 - Replace (E) toilet.
 - Partitions with (N).
 - Patch walls as required.
 - (N) H.C. grab bars.
 - Replace (E) door hardware with H.C. hardware.
 - H.H. door/frame and trim hardware.
 - Reverse door swing - (N) hardware.
 - Remove (E) damaged hardware.
 - Remove cap lines as required.
 - (N) H.C. accessible toilet.
 - (N) mounted lav.
 - Replace (E) thermostats with (N) energy programmable units.
 - (N) wall strip elect. outlets as indicated per electrical drawings.
 - (N) surface mounted.
 - (N) as per electrical drawings.
 - (N) water heater and line.
 - (N) H.C. accessible drinking fountain.
 - (N) drinking fountain.
 - Patch ceiling as required.
 - (N) Taber suspended ceiling with fluorescent luminaires and R-19 insulation.

Unit G

