

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 1 of 42

The purpose of this evaluation report is to establish eligibility for retrofit funding under Proposition 1D (AB 127, 2006). It is not the intent of this evaluation to provide a complete Life Safety evaluation. The evaluation is complete when eligibility has been determined.

## Report Outline

1. Eligibility check summary
2. Evaluation process Appendix A.1. Structural calculations
3. Site and building description Appendix A.2. Evaluation statement notes
4. Deficiency list Appendix A.3 Photographs and details
5. ASCE 31 Evaluation statements



SMITH STRUCTURAL GROUP, LLP

SE Firm Name: Smith Structural Group, LLP  
 SE Address: 811 El Capitan Way, Suite 240  
 San Luis Obispo, CA 93401

Phone: 805-439-2110  
 Email: michael@smithstructural.com



Michael E. Parolini  
 Name of SE whose stamp is above

## 1. Eligibility Check Summary

- |   | <u>YES</u>                          | <u>NO</u>                |
|---|-------------------------------------|--------------------------|
| <b>1.1 Building Occupancy:</b> The building's current or planned use involves regular occupancy by students and staff, as detailed in Section 3.2.  | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| <b>1.2 Structural System:</b> The building's seismic force-resisting system includes at least one of the types listed in Section 3.5.   | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| <b>1.3 Collapse Potential:</b> The building has deficiencies associated with a high potential for local or global collapse in the evaluation earthquake. See Sections 4 and 5 for a list of identified deficiencies. Among the identified deficiencies are the critical items checked in Section 1.3.3: | <input checked="" type="checkbox"/> | <input type="checkbox"/> |
| <b>1.3.1 <input checked="" type="checkbox"/> Collapse Potential Due to Ground Shaking: <math>S_s = 1.18g</math> ASCE 7-05<br/>Occupancy III, Site Class D</b>   |                                     |                          |

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
 SMP Template  
 (iss 09-15-11)  
 (errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 2 of 42

## 1.3.2 Collapse Potential Due to One of the Following Geologic Hazards (CGS Approved Geologic Hazard Report Required):

- LIQUEFACTION
  SLOPE STABILITY FAILURE
  SURFACE FAULT RUPTURE

**UNKNOWN AT THIS TIME**

## 1.3.3 Identified Deficiencies:

- |  |  |  |
|--|--|--|
| <input checked="" type="checkbox"/> LOAD PATH          | <input type="checkbox"/> SHEAR STRESS CHECK (COLUMN) | <input type="checkbox"/> UNREINFORCED MASONRY BEARING WALLS        |
| <input type="checkbox"/> WEAK STORY                    | <input type="checkbox"/> AXIAL STRESS CHECK          |  |
| <input type="checkbox"/> SOFT STORY                    | <input type="checkbox"/> FLAT SLAB FRAMES            | <input type="checkbox"/> SHEAR STRESS CHECK (SHEAR WALL OR INFILL) |
| <input type="checkbox"/> VERTICAL DISCONTINUITIES      | <input type="checkbox"/> CAPTIVE COLUMNS             | <input type="checkbox"/> REDUNDANCY (SHEAR WALL)                   |
| <input type="checkbox"/> MASS                          | <input type="checkbox"/> BEAM BARS                   | <input checked="" type="checkbox"/> OPENINGS AT SHEAR WALLS        |
| <input type="checkbox"/> TORSION                       | <input type="checkbox"/> DEFLECTION COMPATIBILITY    | <input type="checkbox"/> TOPPING SLAB                              |
| <input checked="" type="checkbox"/> ADJACENT BUILDINGS | <input type="checkbox"/> FLAT SLABS                  | <input checked="" type="checkbox"/> WALL ANCHORAGE                 |
| <input type="checkbox"/> MEZZANINES                    | <input type="checkbox"/> REDUNDANCY                  | <input type="checkbox"/> OTHER *                                   |

## 2. Evaluation Process

### 2.1 Purpose and Scope

As described in DSA Procedure 08-03, the primary purpose of this evaluation is to confirm the subject building's eligibility for Proposition 1D (AB 127, 2006) retrofit funding.

As noted in DSA Procedure 08-03, the intent of this evaluation is to identify conditions that represent "a high potential for catastrophic collapse." As described further in Sections 2.2 through 2.4, the evaluation includes:

- Completion of a standardized checklist developed specially for this project (Section 2.2). As described in Section 2.2, once a critical deficiency is confirmed, the balance of the checklist need not be completed.
- A site visit (Section 2.3)
- Document review (Section 2.4)

It is not the intent of this evaluation to provide a complete Life Safety evaluation; earthquake safety hazards other than those listed in this report might exist. Further, it is not the intent of this evaluation to identify deficiencies with respect to post-earthquake use or recovery feasibility. In particular, except where specifically noted, the scope of this evaluation does not include:

- Material testing or destructive investigation
- Comprehensive condition assessment or verification of construction documents
- Assessment of code compliance, either at present or at the time of construction
- Assessment for load combinations not including earthquake effects
- Consideration of Life Safety hazards related to egress
- Consideration of Life Safety hazards related to hazardous materials

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 3 of 42

- Consideration of the effects of damage to nonstructural components or contents.

Building located on sites with geologic hazards (liquefaction, slope failure, faulting) may be eligible for the Proposition 1D funding if it can be demonstrated that the geologic hazard may cause the building to have a high potential for catastrophic collapse. In this case, a geologic hazard report shall be prepared and submitted to CGS for approval and a copy included with evaluation report. The geologic hazard report shall identify the resulting displacements that will be imposed on the structure so a structural analysis can be performed. If eligibility is being sought for a deficiency that is not related to geologic hazards, then a geologic hazard report does not need to be prepared for the purpose of this evaluation report.

With respect to DSA Procedure 08-03, this report fulfills the intent of its Section 1. The remaining sections of Procedure 08-03 are outside the scope of this evaluation and report:

## 2.2 Evaluation criteria: Modifications to ASCE 31

As noted in DSA Procedure 08-03, the evaluation applies ASCE 31<sup>1</sup>, an engineering standard that allows the user to choose a performance level of either Life Safety or Immediate Occupancy. Procedure 08-03 suggests that Life Safety is the performance level of interest, but the Procedure also focuses on collapse, a lesser performance level not explicitly addressed by ASCE 31. For this evaluation, DSA has clarified that only collapse-prone conditions need to be identified. Further, because the focus of this evaluation is on checking eligibility for retrofit funding, as opposed to producing a comprehensive list of potential deficiencies, the full evaluation need not be completed once a critical deficiency is identified.

ASCE 31 involves three “tiers” of evaluation. Tier 1 uses a set of generic, mostly qualitative “evaluation statements” (also called checklists) to identify potential deficiencies. Tier 2 applies more quantitative checks to confirm or correct the Tier 1 findings. Tier 3 involves a more thorough structural analysis. For this evaluation, DSA has clarified that only Tier 1 is required for most issues, with Tier 2 evaluation for specific issues.

The criteria used for this evaluation therefore are based on the ASCE 31 Tier 1 checklists, with the following modifications:

- Basic Structural, Supplemental Structural, and Foundations checklists are considered.
- Nonstructural checklists are excluded. While some issues addressed by these checklists are relevant to nonstructural collapse potential, their completion is beyond the scope of this evaluation. While not considered for purposes of establishing funding eligibility, relevant deficiencies will be investigated and addressed during a retrofit design phase.
- Evaluation statements required by ASCE 31 for Immediate Occupancy only are excluded.
- Evaluation statements not associated with one of the eligible structure types are excluded.
- Certain evaluation statements related to “critical deficiencies” indicative of a high potential for structural collapse are identified. If a critical deficiency is confirmed, the balance of the evaluation need not be completed. The critical deficiencies are those listed in Section 1. They were selected by DSA for this project based in part on precedents set by the California Office of Statewide Health Planning and Development.<sup>2</sup>

<sup>1</sup> *Seismic Evaluation of Existing Buildings* (ASCE/SEI 31-03), American Society of Civil Engineers, 2003.

<sup>2</sup> *2007 California Building Standards Administrative Code (California Code of Regulations, Title 24 Part 1)*, Chapter 6, “Seismic Evaluation Procedures for Hospital Buildings,” Section 1.4.5.1.2, October 23, 2008 Emergency Supplement.

SE Firm Name:	Smith Structural Group, LLP	PR 08-03 SMP Template (iss 09-15-11) (errata 10-11-11)
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401	
SE Firm Phone #:	805-439-2110	

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 4 of 42

- For Quick Checks and Tier 2 evaluations, the ASCE 31 criteria for Life Safety performance are used, except that  $m$  values, where needed, are increased by an additional factor of 1.33.
- The Tier 1 evaluation statements are modified to reflect emphasis on collapse-level performance:
  - Since the presence of an unreinforced masonry bearing wall system is deemed a critical deficiency, an evaluation statement to that effect is added, and detailed ASCE 31 evaluation statements specific to that system are omitted.
  - Condition of Materials: Evaluation statements are edited to focus less on presence of damage and more on significance of damage. Note that Masonry Lay-up and Foundation Performance evaluation statements are relocated to the Condition of Materials subsection of Section 5.
  - Except for cracks in certain concrete members, Condition of Materials evaluation statements related to existing cracks are omitted.
  - Beam Bars: The requirement for 25 percent of the joint bars to be continuous for the length of the member is removed.
  - Redundancy (Moment frame and Braced frame): The requirement for two bays per frame line is removed.
  - Stiffness of wall anchors: The limitation of 1/8-inch gap prior to anchor engagement is removed.
  - Overturning: This statement is removed.
  - In general, statements are modified for clarity and consistency with this DSA program.
- Tier 2 evaluation is required for any critical item (see Section 1) found to be non-compliant by Tier 1. The potential requirement for full-building Tier 2 evaluation found in ASCE 31 Table 3-3 is waived.

## 2.3 Document review

The following documents were provided for use in completing the evaluation, in general compliance with ASCE 31, Section 2.2. The Set ID is used to identify the documents cited in Section 5 of this report.

SETID	DATE	DESCRIPTION
1	1940	Additions to Horace Mann School, Charles H Biggar Architect, 6 sheets, Original Construction of Classroom Addition
2	1989	A-51532 - Horace Mann Modernization, BFGC Architects-Planners, 42 sheets (Classroom Addition Building is referred to as Building 700)

## 2.4 Site visit

In general compliance with ASCE 31, Sections 2.2 and 2.3, a site visit shall be made to verify the building configuration and conditions and to assist in completing the evaluation.

Date of site visit: July 5, 2018  
 Visiting engineer(s) and staff: Jessica Napier, Deryk Izuo  
 School district contact person: Randy Rowles  
 School campus representative  
 (if different than above): same as above

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
 SMP Template  
 (iss 09-15-11)  
 (errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			

The scope of the site visit was based on our judgment, accessibility of certain areas, and convenience of the school on-site liaison. The purpose of the following list is merely to record the work that was done. The site visit included (check all applicable boxes):

- INTERVIEW W/ ON-SITE LIAISON
- GROUNDS, FOR OBSERVATION OF SOIL, SLOPES, DRAINAGE, GENERAL CONDITION
- EXTERIOR OBSERVATION TO VERIFY BASIC MASSING, CONFIGURATION, GENERAL CONDITION
- INTERIOR OBSERVATION TO VERIFY USE, WALL LINE CONFIGURATION, GENERAL CONDITION
- ROOF
- BASEMENT
- CEILING PLENUM
- UNFINISHED SPACES (MECHANICAL ROOMS, CLOSETS, CRAWL SPACES, ETC.)
- DETAILS OF STRUCTURE-ARCHITECTURE INTERACTION
- ROOF-TO-WALL CONNECTIONS
- GRAVITY SYSTEM FRAMING
- SEISMIC FORCE RESISTING SYSTEM ELEMENTS OR COMPONENTS
- ADJACENT BUILDINGS SUBJECT TO POUNDING
- OTHER:

The site visit confirmed that the existing structure generally conforms to the available drawings listed in Section 2.3.

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 6 of 42

## 3. Site and Building Description

### 3.1 Building description

#### General

Year originally built: 1940

DSA Application number A-3234

Original Construction

Work done pursuant to the Garrison Act (Ed Code 17367)

Number of stories above grade: 1

Number of stories below grade: 1

Total floor area (sq ft, approx): 7,300 sq. ft.

Other essentially identical buildings on this campus?  Yes  No

Multipurpose building is of similar construction, designed in 1940. This building is being evaluated with a separate report, as is the URM classroom wing from 1930.

Overhead view of Horace Mann Elementary, taken: July 26, 2018 using Google Earth



SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			

## Photographs

Exterior elevation photograph, looking north, taken August 2, 2018 with Google Earth:



Exterior elevation photograph, looking east, taken August 2, 2018 with Google Earth:




SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 8 of 42

## Ground floor plan



### 3.2 Building Occupancy

Original, current, and planned uses of the building include those indicated here:

	ORIGINAL USE	CURRENT USE	PLANNED FUTURE USE
OFFICE / ADMINISTRATION	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
CLASSROOMS / INSTRUCTION AREAS	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
KITCHEN	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
ASSEMBLY: DINING	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
ASSEMBLY: AUDITORIUM	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
ASSEMBLY: GYMNASIUM	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
LOCKER ROOMS	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
PATIO COVER / BUS SHELTER / WALKWAY COVER	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
BLEACHERS / STADIUM STRUCTURE	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
OTHER OCCUPIED: <i>complete as appropriate</i>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
MECHANICAL / UTILITY ROOMS OR ENCLOSURES	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
BULK STORAGE	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
VACANT / UNUSED	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
OTHER UNOCCUPIED:	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)



# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 9 of 42

## 3.3 Seismicity

Latitude: 35.3769081

Longitude: -118.9574422

Site Class per ASCE 31, Section 3.5.2.3: D

Basis for Site Class determination: Default

Period [sec]	Mapped MCE values from ASCE 7-05 [g]	Site Coefficients from ASCE 31 Tables 3-5, 3-6	Design values per ASCE 31 section 3.5.2.3.1 [g]	$S_a$ per ASCE 31 section 3.5.2.3.1, [g]
0.2	$S_s = 1.18$	$F_a = 1.028$	$S_{DS} = (2/3) S_s F_a = 0.809$	$S_{a,0.2} = S_{DS} = 0.809$
1.0	$S_l = 0.419$	$F_v = 1.581$	$S_{Dl} = (2/3) S_l F_v = 0.441$	$S_{a,1.0} = \min(S_{DS}, S_{Dl}/T) = 0.441$

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 10 of 42

## 3.4 Gravity System

Roof diaphragm and framing:

- Roof diaphragm 1x6 straight sheathing, see Section C on Sheet A10 of Set 2.
- Trussed 2x rafters, see Section C on Sheet A10 of Set 2.
- Trussed roof rafters perpendicular to shear walls are either seated on a concrete ledge or a wood ledger.
  - For OOP loads, no anchorage exists.
  - For IP loads, sheathing is nailed to ledger or blocking, and the ledger or blocking is attached to the concrete with 5/8" diameter bolts at 48" o.c or 60" o.c. See Section C on Sheet A10 of Set 2, as well as Appendix A.3, WALL ANCHORAGE section.
- Where roof rafters are parallel to shear walls
  - For OOP loads, no anchorage exists and there is no corresponding blocking.
  - For IP loads, sheathing is nailed to ledger, and ledger is attached to concrete with 5/8" diameter bolts at 48" or 60" o.c. See Section C on Sheet A10 of Set 2, as well as Appendix A.3, WALL ANCHORAGE section.

Typical floor diaphragm and framing: N/A

Ground floor framing:

- 1 layer of 1x diagonal sheathing with wood finish floor over top (1x straight). See "Cross Section" on Sheet 3 of Set 1 as well as "Section C" on Sheet A10 of Set 2.
- 2x6 floor joists over cripple walls at interior and bearing on wood ledger at exterior concrete stem wall. See same references as above.

Vertical load-bearing elements:

- Exterior bearing walls are 8" reinforced concrete.
- Interior bearing walls are 2x6 wood stud-framed.

Basement walls: N/A, no basement.

Foundation:

- Continuous concrete footings under exterior walls
- Pad footings at interior, under wood cripple walls, see Sheet 1 of Set 1.

Snow load for use in load combinations involving earthquake: N/A, snow load not required.

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 11 of 42

## 3.5 Structural System per ASCE 31 Classifications (Category 2 Buildings Types per AB 300 Report)

	North-South	East-West
C1 Concrete Moment Frames	<input type="checkbox"/>	<input type="checkbox"/>
C1B* Reinforced Concrete Cantilever Columns	<input type="checkbox"/>	<input type="checkbox"/>
C2A Concrete Shear Walls, Flexible Diaphragm	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
C3A Concrete Frame with Infill Masonry Shear Walls, Flexible Diaphragm	<input type="checkbox"/>	<input type="checkbox"/>
PC1 Precast/Tilt-up Concrete Shear Walls, Flexible Diaphragm	<input type="checkbox"/>	<input type="checkbox"/>
PC1A Precast/Tilt-up Concrete Shear Walls, Rigid Diaphragm	<input type="checkbox"/>	<input type="checkbox"/>
PC2 Precast Concrete Frames with Shear Walls, Rigid Diaphragm	<input type="checkbox"/>	<input type="checkbox"/>
PC2A Precast Concrete Frames without Shear Walls, Rigid Diaphragm	<input type="checkbox"/>	<input type="checkbox"/>
RM1 Reinforced Masonry Bearing Walls, Flexible Diaphragm	<input type="checkbox"/>	<input type="checkbox"/>
S1B* Steel Cantilever Columns	<input type="checkbox"/>	<input type="checkbox"/>
S3 Steel Light Frames	<input type="checkbox"/>	<input type="checkbox"/>
URM Unreinforced Masonry Bearing Walls, Flexible Diaphragm	<input type="checkbox"/>	<input type="checkbox"/>
URMA Unreinforced Masonry Bearing Walls, Rigid Diaphragm	<input type="checkbox"/>	<input type="checkbox"/>
M* Mixed Systems - construction containing at least one of the above lateral-force-resisting systems in at least one direction of seismic loading.	<input type="checkbox"/>	<input type="checkbox"/>
None of the above	<input type="checkbox"/>	<input type="checkbox"/>

\* These structural systems are a subset of the classification in ASCE 31 and are defined in the Category 2 building types in the AB 300 Seismic Safety Inventory of California Public Schools report (2002).

### Brief description of structural systems:

Horizontal system combinations	<p>Roof</p> <ul style="list-style-type: none"> <li>• 1x6 diagonal sheathing</li> <li>• Trussed 2x rafters</li> </ul> <p>Floor</p> <ul style="list-style-type: none"> <li>• 1x6 diagonal sheathing</li> <li>• 2x8 floor joists @ 16" o.c.</li> </ul>
Vertical system combinations	<ul style="list-style-type: none"> <li>• 8" reinforced concrete walls</li> <li>• 2x6 wood stud walls, interior</li> </ul>

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 12 of 42

SFRS foundation	Continuous concrete footings
Gravity loading	<p>Approximately half of the gravity loads are carried by the exterior concrete walls, which also act as the SFRS. The remainder of the gravity load is carried by interior wood-framed stud walls.</p> <p>The exceptions to this are the north and south walls of the structure. These walls carry their own self weight, but little roof load.</p>
System details	<p>The SFRS in both directions consists of a wood-framed diaphragm with diagonal sheathing 8" reinforced concrete shear walls</p> <p>Walls are tied to diaphragm for in-plane loads with ledger anchor bolts.</p> <p>Walls are not tied to diaphragm for out-of-plane loads. Nor is there any blocking or other diaphragm support for out-of-plane loads.</p>
Structural materials	<p>1940 Project Specifications – (see Appendix A.3)</p> <p>2,000-psi concrete A15-35 rebar (assume 33-ksi) No. 1 DF grade</p>
Original design code	1937 Uniform Building Code (assumed)
History of seismic retrofit or significant alteration	None
Benchmark year check	Benchmark for C2A structure is 1994

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			

## 4. Deficiency list

The following table summarizes the potential deficiencies identified in Section 5 of this report.

Non-compliant condition	Discussion	Additional evaluation recommended
DETERIORATION OF WOOD	<ul style="list-style-type: none"> <li>• Seen in crawl space</li> <li>• Local collapse mechanism</li> </ul>	None
DETERIORATION OF CONCRETE	<ul style="list-style-type: none"> <li>• Seen in crawl space</li> <li>• Local collapse mechanism</li> </ul>	None
DETERIORATION OF STEEL	<ul style="list-style-type: none"> <li>• Rusted ledger anchor bolts in crawl space</li> <li>• Most likely widespread</li> <li>• Collapse would be local to anchors that fail. Not all anchors are likely to fail at once</li> </ul>	Additional non-destructive investigation
LOAD PATH <i>Critical Item</i>	<ul style="list-style-type: none"> <li>• See “Cross Ties” and “Wall Anchorage” non-compliant conditions</li> <li>• Global collapse mechanisms</li> </ul>	None
ADJACENT BUILDINGS <i>Critical Item</i>	<ul style="list-style-type: none"> <li>• Separation of 6” between adjacent structures is noted on the plans and verified in the field</li> <li>• Local collapse mechanism</li> <li>• It is most likely that pounding will not occur, as the SFRS is concrete shear walls, and a combination of URM and gunite (also very stiff) in the adjacent building</li> </ul>	None
WALL OPENINGS	<ul style="list-style-type: none"> <li>• Wall piers less than 2:1 ratio in most locations</li> <li>• Local collapse mechanism, but could extend to along length of wall with adjacent tall piers</li> </ul>	None
CROSS TIES	<ul style="list-style-type: none"> <li>• Cross ties do not exist where rafters are parallel to shear walls</li> <li>• Global collapse mechanism</li> </ul>	None

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School		
School Address:	2710 Niles Street, Bakersfield, CA 93306	Last Revision Date:	
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:		Page 14 of 42	

UNBLOCKED DIAPHRAGMS	<ul style="list-style-type: none"> <li>Diaphragms are unblocked and 122'-9" max span</li> <li>Global collapse mechanism</li> </ul>	None
WALL ANCHORAGE <i>Critical Item</i>	<ul style="list-style-type: none"> <li>No anchors to resist OOP forces</li> <li>Global collapse mechanism</li> </ul>	None
WOOD LEDGERS	<ul style="list-style-type: none"> <li>Cross grain bending under gravity loads is possible</li> <li>Local collapse mechanism</li> </ul>	None
TIES BETWEEN FOUNDATION ELEMENTS	<ul style="list-style-type: none"> <li>There are no ties between exterior wall continuous footings and interior shallow pier footings</li> <li>Local collapse mechanism</li> </ul>	None

Unknown condition	Discussion	Additional evaluation recommended
REINFORCING STEEL	<ul style="list-style-type: none"> <li>Reinforcing steel was used, according to the project specifications, but there are no notes stating what the reinforcement size and spacing is</li> <li>Global collapse mechanism if walls are under-reinforced</li> </ul>	Additional non-destructive testing
LIQUEFACTION	<ul style="list-style-type: none"> <li>If liquefaction is a hazard on this site, the foundation would not be adequate for supporting the structure</li> <li>Global collapse mechanism</li> </ul>	None
SURFACE FAULT RUPTURE	<ul style="list-style-type: none"> <li>If surface fault rupture is a hazard on this site, the foundation would not be adequate for the soil</li> <li>Global collapse mechanism</li> </ul>	None

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			

## 5. ASCE 31 Evaluation Statements

Evaluation statements provided in this section are from ASCE 31. They have been modified for this project with DSA approval as described in Section 2.2 of this report. References within the evaluation statements to other section numbers are generally to sections of ASCE 31.

C = Compliant

NC = Non-compliant

U = Unknown or not investigated

NA = Not applicable to this building

Items marked NC or U are summarized in Section 4 of this report.

CONDITION OF MATERIALS	
C <input checked="" type="checkbox"/> NC U NA	<p>DETERIORATION OF WOOD. There shall be no evidence of or reason to suspect structural capacity loss due to decay, shrinkage, splitting, fire damage, or sagging in wood members or deterioration, damage, or loosening in metal connection hardware.</p> <p><i>Some water intrusion in the crawl space.</i></p>
C <input checked="" type="checkbox"/> NC U NA	<p>DETERIORATION OF CONCRETE. There shall be no evidence of or reason to suspect structural capacity loss due to cracking of concrete or deterioration of concrete or reinforcing steel in gravity or seismic force-resisting elements.</p> <p><i>Some deterioration in crawl space at stem wall adjacent to crawl space vent on north wall.</i></p>
C <input checked="" type="checkbox"/> NC U NA	<p>DETERIORATION OF STEEL. There shall be no evidence of or reason to suspect structural capacity loss due to rusting, corrosion, cracking, or other deterioration in any of the steel elements or connections in the gravity or seismic force-resisting elements.</p> <p><i>Rust noted on anchor bolt in crawl space.</i></p>
C NC U <input checked="" type="checkbox"/> NA	<p>POST-TENSIONING ANCHORS. There shall be no evidence of or reason to suspect structural capacity loss due to corrosion or spalling in the vicinity of post-tensioning or end fittings. Coil anchors shall not have been used.</p> <p><i>(Post-tensioning not used)</i></p>

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 16 of 42

C NC U <input type="checkbox"/> NA	<p>PRECAST CONCRETE WALLS. There shall be no evidence of or reason to suspect structural capacity loss due to deterioration of concrete or reinforcing steel or distress, especially at connections.</p> <p><i>(Precast concrete not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>MASONRY UNITS. There shall be no evidence of or reason to suspect structural capacity loss due to deterioration of masonry units.</p> <p><i>(Structural masonry not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>MASONRY JOINTS. The mortar shall not be easily scraped away from the joints by hand with a metal tool, and there shall be no evidence of or reason to suspect structural capacity loss due to eroded mortar.</p> <p><i>(Structural masonry not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>MASONRY LAY-UP. Filled collar joints of multi-wythe masonry infill walls shall have negligible voids.</p> <p><i>(Structural masonry not used)</i></p>
<input checked="" type="checkbox"/> NC U NA	<p>FOUNDATION PERFORMANCE. There shall be no evidence of or reason to suspect existing foundation movement (due to settlement, heave, or other causes) that would affect the integrity or strength of the structure.</p> <p><i>Limited cracks in exterior walls</i></p>
<b>BUILDING CONFIGURATION</b>	
C <input checked="" type="checkbox"/> NC U NA <b>Critical Item</b>	<p>LOAD PATH. The structure shall contain a minimum of one complete load path for seismic force effects from any horizontal direction that serves to transfer the inertial forces from the mass to the foundation.</p> <p><i>See WALL ANCHORAGE and CROSS-TIES items in this report.</i></p>
C NC U <input type="checkbox"/> NA <b>Critical Item</b>	<p>WEAK STORY. The strength of the seismic force-resisting system in any story shall not be less than 80% of the strength in an adjacent story, above or below.</p> <p><i>One story</i></p>

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)



# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 17 of 42

<p><b>C NC U <input type="checkbox"/> NA</b></p> <p><b>Critical Item</b></p>	<p>SOFT STORY. The stiffness of the seismic force-resisting system in any story shall not be less than 70% of the seismic force-resisting system stiffness in an adjacent story above or below, or less than 80% of the average seismic force-resisting system stiffness of the three stories above or below.</p> <p><i>One story</i></p>
<p><b>C NC U <input type="checkbox"/> NA</b></p> <p><b>Critical Item</b></p>	<p>GEOMETRY. There shall be no changes in horizontal dimension of the seismic force-resisting system of more than 30% in a story relative to adjacent stories, excluding one-story penthouses and mezzanines.</p> <p><i>One story</i></p>
<p><b><input checked="" type="checkbox"/> NC U NA</b></p> <p><b>Critical Item</b></p>	<p>VERTICAL DISCONTINUITIES. All vertical elements of the seismic force-resisting system shall be continuous to the foundation.</p> <p><i>One story</i></p>
<p><b>C NC U <input type="checkbox"/> NA</b></p> <p><b>Critical Item</b></p>	<p>MASS. There shall be no change in effective mass more than 50% from one story to the next. Light roofs, penthouses and mezzanines need not be considered.</p> <p><i>One story</i></p>
<p><b><input checked="" type="checkbox"/> NC U NA</b></p> <p><b>Critical Item</b></p>	<p>TORSION. The estimated distance between the story center of mass and the story center of rigidity shall be less than 20% of the building width in either plan dimension.</p> <p><i>Building has a flexible diaphragm, and is fairly well balanced with shear wall layout all around the exterior. Openings in the shear walls are consistent, as well.</i></p>

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 18 of 42

<p>C <input checked="" type="checkbox"/> NC <input type="checkbox"/> U <input type="checkbox"/> NA</p> <p><b>Critical Item</b></p>	<p>ADJACENT BUILDINGS. The clear distance between the building being evaluated and any adjacent building shall be greater than 4% of the height of the shorter building. Alternatively, if the 4% separation does not exist, the two buildings shall be configured such that pounding would not damage the columns of the subject building within the clear span of the columns.</p> <p><i>Roof height of original classroom building at west end is 15'-10", and aligns vertically within 12" of 1940 classroom building. There is a 6" separation between the two structures.</i></p> <p><i>15.83' x 4% = 0.63', or 7.6" separation required per this check</i></p> <p><i>Deflection of concrete shear wall structure and the URM/gunite structure would be much lower than other SFRS systems. Therefore, although the buildings may move toward each other in a seismic event, the chance of them pounding with the current 6" separation is very low. Tier 2 check not performed.</i></p>
<p>C <input type="checkbox"/> NC <input type="checkbox"/> U <input checked="" type="checkbox"/> NA</p> <p><b>Critical Item</b></p>	<p>MEZZANINES. Interior mezzanine levels shall be braced independently from the main structure, or shall be anchored to the seismic force-resisting elements of the main structure.</p> <p><i>(Mezzanines not used)</i></p>
<p><b>MOMENT FRAMES</b></p>	
<p>C <input type="checkbox"/> NC <input type="checkbox"/> U <input checked="" type="checkbox"/> NA</p> <p><b>Critical Item</b></p>	<p>SHEAR STRESS CHECK (Columns). The shear stress in concrete columns of the seismic force-resisting system, calculated using the Quick Check procedure of Section 3.5.3.2, shall be less than the greater of 100 psi or <math>2\sqrt{f'_c}</math>.</p> <p><i>(Moment frames not used)</i></p>
<p>C <input type="checkbox"/> NC <input type="checkbox"/> U <input checked="" type="checkbox"/> NA</p> <p><b>Critical Item</b></p>	<p>AXIAL STRESS CHECK (Concrete columns). The axial stress due to gravity loads in columns subjected to seismic overturning forces shall be less than <math>0.10f'_c</math>. Alternatively, the axial stresses due to overturning forces alone, calculated using the Quick Check procedure of Section 3.5.3.6, shall be less than <math>0.30f'_c</math>.</p> <p><i>(Moment frames not used)</i></p>
<p>C <input type="checkbox"/> NC <input type="checkbox"/> U <input checked="" type="checkbox"/> NA</p> <p><b>Critical Item</b></p>	<p>AXIAL STRESS CHECK (Steel columns). The axial stress due to gravity loads in steel columns subjected to seismic overturning forces shall be less than <math>0.10F_y</math>. Alternatively, the axial stresses due to overturning forces alone, calculated using the Quick Check procedure of Section 3.5.3.6, shall be less than <math>0.30F_y</math>.</p> <p><i>(Moment frames not used)</i></p>

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 19 of 42

<p>C NC U <input type="checkbox"/> NA</p> <p><b>Critical Item</b></p>	<p>FLAT SLAB FRAMES. The seismic force-resisting system shall not be a frame consisting of columns and a flat slab/plate without beams.</p> <p><i>(Moment frames not used)</i></p>
<p>C NC U <input type="checkbox"/> NA</p>	<p>PRESTRESSED FRAME ELEMENTS. The seismic force-resisting frames shall not include any prestressed or post-tensioned elements where the average prestress exceeds the lesser of 700 psi or <math>f'c/6</math> at potential hinge locations. The average prestress shall be calculated in accordance with the Quick Check Procedure of Section 3.5.3.8.</p> <p><i>(Moment frames not used)</i></p>
<p>C NC U <input type="checkbox"/> NA</p> <p><b>Critical Item</b></p>	<p>CAPTIVE COLUMNS. There shall be no columns at a level with height/depth ratios less than 50% of the nominal height/depth ratio of the typical columns at that level.</p> <p><i>(Moment frames not used)</i></p>
<p>C NC U <input type="checkbox"/> NA</p>	<p>NO SHEAR FAILURES. The shear capacity of frame members in the seismic force-resisting system shall be able to develop the moment capacity at the ends of the members.</p> <p><i>(Moment frames not used)</i></p>
<p>C NC U <input type="checkbox"/> NA</p>	<p>STRONG COLUMN/WEAK BEAM. The sum of the moment capacity of the columns shall be 20% greater than that of the beams at concrete frame joints.</p> <p><i>(Moment frames not used)</i></p>
<p>C NC U <input type="checkbox"/> NA</p>	<p>STRONG COLUMN/WEAK BEAM. The percent of strong column/weak beam joints in each story of each line of steel moment-resisting frames shall be greater than 50%. This check need not apply for 1-story structures.</p> <p><i>(Moment frames not used)</i></p>
<p>C NC U <input type="checkbox"/> NA</p> <p><b>Critical Item</b></p>	<p>BEAM BARS. At least two longitudinal top and two longitudinal bottom bars shall extend continuously throughout the length of each frame beam.</p> <p><i>(Moment frames not used)</i></p>

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 20 of 42

C NC U <input type="checkbox"/> NA	<p>COLUMN BAR SPLICES. All column bar lap splice lengths shall be greater than <math>35d_b</math>, and shall be enclosed by ties spaced at or less than <math>8d_b</math>. Alternatively, column bars shall be spliced with mechanical couplers with a capacity of at least 1.25 times the nominal yield strength of the spliced bar.</p> <p><i>(Moment frames not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>BEAM BAR SPLICES. The lap splices or mechanical couplers for longitudinal beam reinforcing shall not be located within <math>l_b/4</math> of the joints and shall not be located in the vicinity of potential plastic hinge locations.</p> <p><i>(Moment frames not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>COLUMN TIE SPACING. Frame columns shall have ties spaced at or less than <math>d/4</math> throughout their length and at or less than <math>8d_b</math> at all potential plastic hinge locations.</p> <p><i>(Moment frames not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>STIRRUP SPACING. All beams shall have stirrups spaced at or less than <math>d/2</math> throughout their length. At potential plastic hinge locations stirrups shall be spaced at or less than the minimum of <math>8d_b</math> or <math>d/4</math>.</p> <p><i>(Moment frames not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>JOINT REINFORCING. Beam-column joints shall have ties spaced at or less than <math>8d_b</math>.</p> <p><i>(Moment frames not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>COMPLETE FRAMES. Concrete frames that are not part of the seismic force-resisting system shall form a complete gravity load carrying system.</p> <p><i>(Moment frames not used)</i></p>
C NC U <input type="checkbox"/> NA <b>Critical Item</b>	<p>DEFLECTION COMPATIBILITY. Elements of concrete frames that are not part of the seismic force-resisting system shall have the shear capacity to develop the flexural strength of the components.</p> <p><i>(Moment frames not used)</i></p>

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 21 of 42

C NC U <input type="checkbox"/> NA	<p>FLAT SLABS. Flat slabs/plates that are not part of the seismic force-resisting system shall have continuous bottom steel through the column joints.</p> <p><i>(Moment frames not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>REDUNDANCY (Moment frame). The number of lines of moment frames in each principal direction shall be greater than or equal to 2.</p> <p><i>(Moment frames not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>INTERFERING WALLS. All concrete and masonry infill walls placed in moment frames shall be isolated from structural elements. (This evaluation statement does not apply to seismic force-resisting system type C3A or others where the infill is being evaluated as a shear wall or force-resisting element.)</p> <p><i>(Moment frames not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>PRECAST CONNECTION CHECK. The connections at joints of precast concrete frames shall have the capacity to resist the shear and moment demands calculated using the Quick Procedure of Section 3.5.3.5</p> <p><i>(Moment frames not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>PRECAST FRAMES. For buildings with concrete shear walls, precast concrete frame elements shall not be necessary as primary components for resisting seismic forces.</p> <p><i>(Moment frames not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>PRECAST CONNECTIONS. For buildings with concrete shear walls, the connections between precast frame elements such as chords, ties, and collectors in the seismic force-resisting system shall develop the capacity of the connected members.</p> <p><i>(Moment frames not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>DRIFT CHECK: The drift ratio of the steel moment frames, calculated using the Quick Check procedure of Section 3.5.3.1, shall be less than 0.025.</p> <p><i>(Moment frames not used)</i></p>

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 22 of 42

C NC U <input type="checkbox"/> NA	<p>MOMENT-RESISTING CONNECTIONS: All moment connections shall be able to develop the strength of the adjoining members or panel zones.</p> <p><i>(Moment frames not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>PANEL ZONES: All panel zones shall have the shear capacity to resist the shear demand required to develop 0.8 times the sum of the flexural strengths of the girders framing in at the face of the column.</p> <p><i>(Moment frames not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>COLUM SPLICES: All column splice details located in moment-resisting frames shall include connection of both flanges and the web.</p> <p><i>(Moment frames not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>COMPACT MEMBERS: All frame elements shall meet section requirements set forth by Table I-9-1 of Seismic Provisions for Structural Steel Buildings (AISC, 1997).</p> <p><i>(Moment frames not used)</i></p>
<b>SHEAR WALLS</b>	
C NC U <input type="checkbox"/> NA <b>Critical Item</b>	<p>UNREINFORCED MASONRY BEARING WALLS. The seismic force-resisting system in any direction shall not rely on or consist primarily of unreinforced masonry bearing walls.</p> <p><i>(URM not used)</i></p>
<input checked="" type="checkbox"/> NC U NA <b>Critical Item</b>	<p>SHEAR STRESS CHECK (Shear wall). The shear stress in the concrete shear walls, calculated using the Quick Check procedure of Section 3.5.3.3, shall be less than the greater of 100 psi or <math>2\sqrt{f'_c}</math>.</p> <p><i>See Appendix A.1 for load take-off and Appendix A.2 for calculations. The concrete passes this shear stress check.</i></p>

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 23 of 42

C NC <input type="checkbox"/> NA	<p>REINFORCING STEEL. In concrete or precast shear walls, the ratio of reinforcing steel area to gross concrete area shall be not less than 0.0015 in the vertical direction and 0.0025 in the horizontal direction. The spacing of reinforcing steel shall be equal to or less than 18 inches.</p> <p><i>Specifications found in DSA archives do give instructions for reinforcement. However, drawings do not indicate size and spacing.</i></p>
C NC U <input type="checkbox"/> NA	<p>COUPLING BEAMS. The stirrups in coupling beams over means of egress shall be spaced at or less than d/2 and shall be anchored into the confined core of the beam with hooks of 135° or more.</p> <p><i>One story</i></p>
<input checked="" type="checkbox"/> NC U NA Critical Item	<p>REDUNDANCY (Shear wall). The number of lines of shear walls in each principal direction shall be greater than or equal to 2.</p> <p><i>Shear walls at all exterior walls.</i></p>
C NC U <input type="checkbox"/> NA	<p>PROPORTIONS. The height-to-thickness ratio of masonry infill walls at each story shall be less than 9. (This evaluation statement applies only to seismic force-resisting system type C3A and others where the infill is being evaluated as a shear wall or force-resisting element.)</p> <p><i>(Masonry infill not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>SOLID WALLS. The masonry infill walls shall not be of cavity construction. (This evaluation statement applies only to seismic force-resisting system type C3A and others where the infill is being evaluated as a shear wall or force-resisting element.)</p> <p><i>(Masonry infill not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>INFILL WALLS. The infill walls shall be continuous to the soffits of the frame beams and to the columns to either side. (This evaluation statement applies only to seismic force-resisting system type C3A and others where the infill is being evaluated as a shear wall or force-resisting element.)</p> <p><i>(Masonry infill not used)</i></p>

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 24 of 42

C NC U <input type="checkbox"/> NA	<p><b>Critical Item</b></p> <p>SHEAR STRESS CHECK (Precast concrete shear walls). The shear stress in the precast panels, calculated using the Quick Check procedure of Section 3.5.3.3, shall be less than the greater of 100 psi or <math>2\sqrt{f_c}</math>.</p> <p><i>(Precast concrete not used)</i></p>
C <input type="checkbox"/> NC U NA	<p>WALL OPENINGS. The total width of openings along any perimeter wall line shall constitute less than 75% of the length of any perimeter shear wall, with the <u>wall piers having height-to-width ratios of less than 2 to 1.</u></p> <p><i>Typical wall pier height-to-width ratio is 6.4, between windows on the east and west exterior walls.</i></p>
<input checked="" type="checkbox"/> NC U NA	<p>CORNER OPENINGS. Walls with openings at a building corner larger than the width of a typical panel shall be connected to the remainder of the wall with collector reinforcing.</p>
C NC U <input type="checkbox"/> NA	<p><b>Critical Item</b></p> <p>SHEAR STRESS CHECK (Brick or hollow clay masonry infill). The shear stress in the masonry shear walls, calculated using the Quick Check procedure of Section 3.5.3.3, shall be less than 30 psi for clay units.</p> <p><i>(Masonry shear walls not used)</i></p>
C NC U <input type="checkbox"/> NA	<p><b>Critical Item</b></p> <p>SHEAR STRESS CHECK (Concrete block infill and reinforced masonry shear walls). The shear stress in the masonry shear walls, calculated using the Quick Check procedure of Section 3.5.3.3, shall be less than 70 psi for concrete units.</p> <p><i>(Masonry shear walls not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>PROPORTIONS. The height-to-thickness ratio of unreinforced masonry infill shear walls shall be less than the following: Top story of multi-story building: 9, First story of multi-story building: 15, All other conditions: 13</p> <p><i>(Masonry shear walls not used)</i></p>
C NC U <input type="checkbox"/> NA	<p>REINFORCING STEEL. In reinforced masonry shear walls, the total vertical and horizontal reinforcing steel ratio shall be greater than 0.002 of the wall with the minimum of 0.0007 in either of the two directions; the spacing of reinforcing steel shall be less than 48"; and all vertical bars shall extend to the top of the walls.</p> <p><i>(Masonry shear walls not used)</i></p>

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)



# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 25 of 42

## BRACED FRAMES

C NC U <input type="checkbox"/> NA	REDUNDANCY: The number of lines of braced frames in each principal direction shall be greater than or equal to 2.  <i>(Braced frames not used)</i>
C NC U <input type="checkbox"/> NA	AXIAL STRESS CHECK: The axial stress in the diagonals, calculated using the Quick Check Procedure of Section 3.5.3.4, shall be less than $0.50F_y$ .  <i>(Braced frames not used)</i>
C NC U <input type="checkbox"/> NA	SLENDERNESS OF DIAGONALS: All diagonal elements required to carry compression shall have $Kl/r$ ratios less than 120.  <i>(Braced frames not used)</i>
C NC U <input type="checkbox"/> NA	CONNECTION STRENGTH: All the brace connections shall develop the yield capacity of the diagonals.  <i>(Braced frames not used)</i>
C NC U <input type="checkbox"/> NA	K-BRACING: The bracing system shall not include K-braced bays.  <i>(Braced frames not used)</i>

## DIAPHRAGMS

<input checked="" type="checkbox"/> NC U NA	DIAPHRAGM CONTINUITY. The diaphragm shall not be composed of split-level floors and shall not have expansion joints.
C <input checked="" type="checkbox"/> U NA	CROSS TIES. There shall be continuous cross ties between diaphragm chords.  <i>Cross ties do not appear to exist where roof rafters are parallel to shear walls.</i>

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 26 of 42

<input checked="" type="checkbox"/> NC U NA	<p>ROOF CHORD CONTINUITY. All roof chord elements shall be continuous, regardless of changes in roof elevation.</p> <p><i>Although the reinforcement size and spacing is unknown, it is highly likely that horizontal rebar is placed consistently close to the diaphragm level, and therefore, the roof chord elements are continuous.</i></p>
<input type="checkbox"/> NC U <input checked="" type="checkbox"/> NA <b>Critical Item</b>	<p>OPENINGS AT SHEAR WALLS. Diaphragm openings immediately adjacent to the shear walls shall be less than 25% of the wall length, and diaphragm openings immediately adjacent to exterior masonry shear walls shall not be greater than 8 ft long.</p> <p><i>Skylights are not immediately adjacent to shear walls. See "Roof Plan" on Sheet 1 of Set 1.</i></p>
<input type="checkbox"/> NC U <input checked="" type="checkbox"/> NA	<p>OPENINGS AT BRACED FRAMES. Diaphragm openings immediately adjacent to the braced frames shall extend less than 25% of the frame length.</p> <p><i>(Braced frames not used)</i></p>
<input type="checkbox"/> NC U <input checked="" type="checkbox"/> NA	<p>OTHER DIAPHRAGMS. The diaphragm shall not consist of a system other than wood, metal deck, concrete or horizontal bracing.</p> <p><i>Wood diaphragms used</i></p>
<input type="checkbox"/> NC U <input checked="" type="checkbox"/> NA <b>Critical Item</b>	<p>TOPPING SLAB. Precast concrete diaphragm elements shall be interconnected by a continuous reinforced concrete topping slab.</p> <p><i>(Topping slab not used)</i></p>
<input type="checkbox"/> NC U <input checked="" type="checkbox"/> NA	<p>STRAIGHT SHEATHING. All straight sheathed diaphragms shall have aspect ratios less than 2 to 1 in the direction being considered.</p> <p><i>Diagonal sheathing is used</i></p>
<input checked="" type="checkbox"/> NC U NA	<p>SPANS. All wood diaphragms with spans greater than 24 ft shall consist of wood structural panels or diagonal sheathing.</p> <p><i>Diagonal sheathing is used</i></p>

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 27 of 42

C <input checked="" type="checkbox"/> NC <input type="checkbox"/> U <input type="checkbox"/> NA	<p>UNBLOCKED DIAPHRAGMS. All diagonally sheathed or unblocked wood structural panel diaphragms shall have horizontal spans less than 40 ft and shall have aspect ratios less than or equal to 4 to 1.</p> <p><i>In north-south loading direction, diaphragm spans 122'-9". See Sheet 2 of Set 1.</i></p>
<b>CONNECTIONS</b>	
C <input checked="" type="checkbox"/> NC <input type="checkbox"/> U <input type="checkbox"/> NA <b>Critical Item</b>	<p>WALL ANCHORAGE. Exterior concrete or masonry walls shall be anchored for out-of-plane forces at each diaphragm level with steel anchors, reinforcing dowels, or straps developed into the diaphragm. Connections shall have adequate strength to resist the connection force calculated in the Quick Check procedure of Section 3.5.3.7.</p> <p><i>Walls are not anchored for OOP forces. Anchorage is used in the wood ledgers to provide gravity load and in-plane load transfer. See "Wood Ledgers" topic, below. There is no indication of OOP anchorage in Set 1, Set 2, the Specifications, or the DSA review. Furthermore, the 1930 and 1937 structures by the same architect did not have OOP anchorage.</i></p>
C <input checked="" type="checkbox"/> NC <input type="checkbox"/> U <input type="checkbox"/> NA	<p>WOOD LEDGERS. The connection between the wall panels and the diaphragm shall not induce cross-grain bending or tension in the wood ledgers.</p> <p><i>Wood ledgers are attached with 5/8" diameter bolts at 48" o.c. or 60" o.c., as stated in the DSA Structural Engineer's Correction List from April 6, 1940. Please see Appendix A.3. and Item #9.b. It is not likely in this configuration that the anchor bolts were staggered so as to avoid cross-grain bending.</i></p>
C <input type="checkbox"/> NC <input type="checkbox"/> U <input checked="" type="checkbox"/> NA	<p>PRECAST PANEL CONNECTIONS. There shall be at least two anchors from each precast wall panel into the diaphragm elements.</p> <p><i>(Precast panels not used)</i></p>
C <input type="checkbox"/> NC <input checked="" type="checkbox"/> U <input type="checkbox"/> NA	<p>STIFFNESS OF WALL ANCHORS. Anchors of concrete or masonry walls to wood structural elements shall be installed taut and shall be stiff enough to limit the relative movement between the wall and the diaphragm prior to engagement of the anchors, as needed for reliable bearing.</p>
C <input type="checkbox"/> NC <input type="checkbox"/> U <input checked="" type="checkbox"/> NA	<p>GIRDER/COLUMN CONNECTION. There shall be a positive connection utilizing plates, connection hardware, or straps between girders and their supporting columns. (This evaluation statement applies primarily to precast concrete and masonry systems.)</p>

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 28 of 42

C NC U <input type="checkbox"/> NA	GIRDERS. Girders supported by walls or pilasters shall have at least two additional column ties securing the anchor bolts. (This evaluation statement applies primarily to precast concrete systems.)  <i>(Precast frame not used)</i>
C NC U <input type="checkbox"/> NA	CORBEL BEARING. If precast concrete frame girders bear on column corbels, the length of bearing shall be greater than 3".  <i>(Precast frame not used)</i>
C NC U <input type="checkbox"/> NA	CORBEL CONNECTIONS. Precast concrete frame girders shall not be connected to corbels with welded elements.  <i>(Precast frame not used)</i>
<input checked="" type="checkbox"/> NC U NA	TRANSFER TO SHEAR WALLS. Diaphragms shall be connected for transfer of loads to shear walls.  <i>It can reasonably be assumed that the diagonal sheathing is nailed to the ledger and that the ledger is bolted to the concrete shear wall. This is the method used in the adjacent 1930 URM building and the adjacent 1937 C2A building by the same architect. Section C, Sheet A10 of Set 2 does show ledgers.</i>
C NC U <input type="checkbox"/> NA	TRANSFER TO STEEL FRAMES. Diaphragms shall be connected for transfer of loads to the steel frames.  <i>(Steel frames not used)</i>
C NC U <input type="checkbox"/> NA	TOPPING SLAB TO WALLS OR FRAMES. Reinforced concrete topping slabs that interconnect the precast concrete diaphragm elements shall be doweled for transfer of forces into shear wall or frame elements.  <i>(Topping slab not used)</i>
C NC U <input type="checkbox"/> NA	CONCRETE COLUMNS. All concrete columns shall be doweled into the foundation.  <i>(Concrete columns not used)</i>

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 29 of 42

<input checked="" type="checkbox"/> NC U NA	FOUNDATION DOWELS. Wall reinforcement shall be doweled into the foundation.  <i>This detail is unknown, but it can reasonably be assumed that the concrete wall is doweled to the footings. This is the method used in the adjacent 1937 C2A building by the same architect.</i>
C NC U <input type="checkbox"/> NA	PRECAST WALL PANELS. Precast wall panels shall be connected to the foundation.  <i>(Precast panels not used)</i>
C NC U <input type="checkbox"/> NA	UPLIFT AT PILE CAPS. Pile caps shall have top reinforcement and piles shall be anchored to the pile caps.  <i>(Piles not used)</i>
C NC U <input type="checkbox"/> NA	STEEL COLUMNS: The columns in lateral-force-resisting frames shall be anchored to the building foundation.  <i>(Steel frames not used)</i>
C NC U <input type="checkbox"/> NA	WALL PANELS: Metal, fiberglass or cementitious wall panels shall be positively attached to the foundation.  <i>(Cladding panels not used)</i>
C NC U <input type="checkbox"/> NA	ROOF PANELS: Metal, plastic, or cementitious roof panels shall be positively attached to the roof framing to resist seismic forces.  <i>(Cladding panels not used)</i>
C NC U <input type="checkbox"/> NA	WALL PANELS: Metal, fiberglass or cementitious wall panels shall be positively attached to the framing to resist seismic forces.  <i>(Cladding panels not used)</i>  <i>The brick veneer is most likely anchored per the requirements in the project specifications. See Appendix A.3.</i>

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 30 of 42

## FOUNDATION

C NC U <input checked="" type="checkbox"/> NA	POLE FOUNDATIONS. Pole foundations shall have a minimum embedment depth of 4 ft.  <i>Foundations are conventional concrete continuous and pad footings as well as shallow piers.</i>
C <input checked="" type="checkbox"/> U NA	TIES BETWEEN FOUNDATION ELEMENTS. The foundation shall have ties adequate to resist seismic forces where footings, piles, and piers are not restrained by beams, slabs, or soils in Site Class A, B, or C.  <i>Interior pier footings not tied.</i>

## GEOLOGIC SITE HAZARDS

C NC <input checked="" type="checkbox"/> NA <b>Critical Item</b>	LIQUEFACTION: Liquefaction-susceptible, saturated, loose granular soils that could jeopardize the building's seismic performance shall not exist in the foundation soils at depths within 50 feet.
C NC U <input checked="" type="checkbox"/> NA <b>Critical Item</b>	SLOPE FAILURE: The building site shall be sufficiently remote from potential earthquake-induced slope failures or rockfalls to be unaffected by such failures or shall be capable of accommodating any predicted movements without failure.
C NC <input checked="" type="checkbox"/> NA <b>Critical Item</b>	SURFACE FAULT RUPTURE: Surface fault rupture and surface displacement at the building site is not anticipated.

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 31 of 42

## Appendices

### A.1 Structural calculations

#### UNIT WEIGHTS

CLASSROOM ADDITION UNIT WEIGHT BREAKDOWN	
<u>ROOF</u>	
ROOFING	3.0 PSF
1x SHTG	2.25 PSF
2x4 @ 24" o.c.	0.75 PSF
2x16 @ 24" o.c.	2.5 PSF
BATT INSULATION	1.0 PSF
PLASTER CEILING	8.0 PSF
MEP	0.5 PSF
SPRINKLERS	0.5 PSF
	18.5 PSF
<u>WALLS</u>	
8" CONC. WALL = $150 \text{ PCF} (8 \times 12) =$	100 PSF
BRICK VENEER =	50 PSF

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 32 of 42


## ATC HAZARDS RESPONSE SPECTRUM INFORMATION

### ATC Hazards by Location


#### Search Information

**Address:** 2710 Niles St, Bakersfield, CA 93306, USA  
**Coordinates:** 35.37690810000001, -118.9574422  
**Timestamp:** 2018-07-16T17:06:25.321Z  
**Hazard Type:** Seismic  
**Reference Document:** ASCE7-05  
**Risk Category:** III  
**Site Class:** D  
**Report Title:** Horace Mann Elementary School


#### Map Results



MCE<sub>R</sub> Horizontal Response Spectrum



Design Horizontal Response Spectrum



#### Text Results

##### Basic Parameters

Name	Value	Description
S <sub>S</sub>	1.18	MCE <sub>R</sub> ground motion (period=0.2s)
S <sub>1</sub>	0.419	MCE <sub>R</sub> ground motion (period=1.0s)
S <sub>MS</sub>	1.213	Site-modified spectral acceleration value
S <sub>M1</sub>	0.662	Site-modified spectral acceleration value
S <sub>DS</sub>	0.809	Numeric seismic design value at 0.2s SA
S <sub>D1</sub>	0.441	Numeric seismic design value at 1.0s SA

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
 SMP Template  
 (iss 09-15-11)  
 (errata 10-11-11)



# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			

## ATC HAZARDS RESPONSE SPECTRUM INFORMATION (continued)

SDC	D	Seismic design category
F <sub>a</sub>	1.028	Site amplification factor at 0.2s
F <sub>v</sub>	1.581	Site amplification factor at 1.0s
T <sub>L</sub>	12	Long-period transition period (s)

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 34 of 42

## BASE SHEAR/PSEUDO-LATERAL FORCE

PSEUDO LATERAL FORCE

$$V = C S_a W \quad \text{ASCE 31, EQN. 3-1}$$

$$S_a = \frac{S_{D1}}{T}, \text{ BUT } \leq S_{DS} \quad \text{\S EQN. 3-4}$$

$$= 2.44$$

$$\therefore S_a = S_{DS} = 0.773g$$

$$S_{DS} = 0.773g$$

$$S_{D1} = 0.427g$$

$$T = C_t h_n^B \quad \text{\S EQN. 3-8}$$

$$C_t = 0.020$$

$$h_n = 18'$$

$$B = 0.75 \quad \text{\S SEC. 3.2.2.4}$$

$$T = 0.175s$$

$C = 1.0 \quad \text{\S TABLE 3-4}$

$W = \text{EFFECTIVE SEISMIC WEIGHT}$

$$W_{\text{ROOF}} = 7,000 \text{ ft}^2 (18.5 \text{ PSF}) = 129.5 \text{ K}$$

$$W_{\text{WALLS}} = 6' (100 \text{ PSF}) \times 360' + 5' (100 \text{ PSF}) (0.7) \times 360'$$

$$= 162 \text{ K}$$

$$W_{\text{BRICK VEN.}} = 6' (50 \text{ PSF}) \times 240' + 5' (50 \text{ PSF}) (0.7) \times 240'$$

$$= 114 \text{ K}$$


---


$$W_{\text{TOTAL}} = 406 \text{ K}$$

$$V = 1.0 (0.809) (406 \text{ K}) \longrightarrow \underline{V = 329 \text{ K}}$$

SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 35 of 42

## A.2 Evaluation statement notes

### SHEAR STRESS (Concrete)

STRESS IN SHEARWALLS

$$V_j^{AVG} = \frac{1}{m} \left( \frac{V_j}{A_w} \right) \quad \text{§EQN. 3-12} \quad V_j = V = 829K$$

AW OF WALLS IN EACH DIRECTION

SOUTH WALLS:  $8'' \times (120' - 18(4.5')) = 3,744in^2$  32.5% SOLID

NORTH WALLS:  $8'' \times (120' - 18(4.5')) = 3,744in^2$  32.5% SOLID

EAST WALLS:  $8'' \times (59' - 10') = 4,704in^2$  83.0% SOLID

WEST WALLS:  $8'' \times (59' - 6') = 5,088in^2$  89.0% SOLID

$$V_j @ N/S WALLS = \frac{829K}{2} = 165K \quad m=4.0, \text{ CONC. § TABLE 3-1}$$

$$V_{AVG} = \frac{1}{4.0} \left( \frac{165K}{3,744in^2} \right) = \underline{0.012 ksi (12psi)}$$

100psi OR  $2\sqrt{f'_c}$  IS MAX SHEAR STRESS ALLOWED

$$2\sqrt{2,000psi} = 89psi \text{ ALLOWED}$$

FACTOR FROM DSA  $\rightarrow \frac{12psi}{1.33} = 10psi$  IS APPLIED

$\therefore 10psi < 89psi, \text{ O.K.}$


SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			

## A.3 Photographs and details (not used)

### Structural Materials (Reinforced Concrete Specification, first page)




SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			

## Structural Materials (Reinforced Concrete Specification, fourth page)




SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 38 of 42

Structural Materials (Reinforced Concrete Specification, seventh page)




SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
 SMP Template  
 (iss 09-15-11)  
 (errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 39 of 42

Structural Materials (Carpenter and Mill Work Specification, second page)




SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 40 of 42

Structural Materials (Carpenter and Mill Work Specification, third page)



SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110


PR 08-03  
 SMP Template  
 (iss 09-15-11)  
 (errata 10-11-11)



# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 41 of 42

WOOD LEDGERS (see item #9.b)




SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)

# ELIGIBILITY EVALUATION REPORT

School District:	Bakersfield City School District	Original Report Date:	August 27, 2018
School Campus:	Horace Mann Elementary School	Last Revision Date:	
School Address:	2710 Niles Street, Bakersfield, CA 93306		
Building Name/ID:	A-3234 1940 Classroom Addition		
Project Tracking No.:			Page 42 of 42

## WALL PANELS (from Project Specifications)



SE Firm Name:	Smith Structural Group, LLP
SE Firm Address:	811 El Capitan Way, Suite 240, San Luis Obispo, CA, 93401
SE Firm Phone #:	805-439-2110

PR 08-03  
SMP Template  
(iss 09-15-11)  
(errata 10-11-11)