



- KEYNOTES** **CBC 1998** **PC**
- EXTERIOR FLYWOOD SIGN/WEATHERING - NAIL W/ CORROSION RESISTANT 24 BOX NAILS @ 4" O.C. BOUNDARY & SERIES, AND 12" O.C. FIELD, WITH MOISTURE BARRIER SEE SHEET 4.0 FOR MATERIAL.
 - TYPICAL INTERIOR FINISH - SEE SHEET 4.1 FOR MATERIAL.
 - STEEL TUBE COLUMN - SEE SHEET 8.0 OR 8.1
 - SEALANT
 - 1/2" TYP DIST-PS OR RANBET 24 50 @ 24" O.C.
 - 2x4 TRIMMER
 - 2x4 WALL HEIGHT STUDS
 - 2x4 TOP PLATE
 - 2x4 BOTTOM PLATE
 - ROOF SHEATHING - SEE SHEET 8.0 OR 8.1
 - FLOOR SHEATHING - SEE SHEET 8.0 OR 8.1
 - GALVANIZED METAL FLASHING
 - 1/2" BOX NAILS @ 12" O.C.
 - NOT USED
 - STEEL FLOOR CHANNEL - SEE SHEET 8.0 OR 8.1
 - STEEL JOIST - SEE SHEET 8.0 OR 8.1
 - HOLLOW METAL DOOR FRAME
 - METAL DOOR
 - MOISTURE BARRIER
 - HEADER - (2) 2x4 1/2" STD GRD. PLAT
 - DOOR BOTTOM WITH HEATHER STRIP
 - ALUMINUM THRESHOLD
 - MOUNTED AAC
 - 4x4 1/2" 4 BETTER POST
 - 2x4 BLOCK BETWEEN STUDS. ATTACH TO STUDS W/ 24 1/2" BOX NAILS EACH END OF BLOCKS INTO STD
 - NOT USED.
 - 1/2" x 2" LONG STEEL BOTTOM BRACKET
 - NOT USED.
 - 3/8" DIA. x 2-1/2" LAG BOLTS, GRTY AS INDICATED BY PRE DRILLED HOLES ON LIST.
 - 5/4" x SPACER
 - NOT USED
 - NOT USED
 - 1/4" TRIM
 - NOT USED
 - NOT USED
 - NOT USED
 - VINYL WRAPPED GLOSS OFF BATT. ATTACH W/ 24 FRESH NAILS @ 12" O.C. (2) @ TOP, & 8" W.
 - NOT USED
 - SPACER/HEADER @ PERIM. OF OVERHANG.
 - ROOFING-SEE SHEET 4.1
 - 24 50 OUTER - SEE ROOF PLAN FOR LOCATION

NOTES:
WIND BUILDING WIND LOAD IS 60 MPH WIND D.F. #2 WOOD MEMBERS.

IDENTIFICATION STAMP
DIV. OF THE STATE ARCHITECT
A 03 117375
AC / FLS / SS / 84
Date - JUL 27 2016

D.S.A.

04-101065

D.S.A.

PORTION 1

STRUCT. ENGINEER

ARCHITECT

CHANGE ORDER

CHECKED BY

TURORA MODULAR INDUSTRIES

TYPICAL DETAILS

PLY/ND EXTERIOR

(WOOD STUDS)

SS.O