

GENERAL SPECIFICATIONS

1. MATERIALS AND WORKMANSHIP: ALL WORK SHALL BE DONE TO THE BEST QUALITY...

2. GENERAL DESIGN REQUIREMENTS: EACH MODULE SHALL BE PERMANENTLY IDENTIFIED WITH A METAL IDENTIFICATION TAG...

3. DIMENSIONS: THE BUILDING SHALL CONSIST OF 960 SQUARE FEET WITH A TOLERANCE OF PLUS OR MINUS 5 SQUARE FEET...

4. FRAMING: FRAMING AND STRUCTURAL MEMBERS SHALL BE OF THE TYPE, GRADE, AND SIZE INDICATED IN THE STRUCTURAL DRAWINGS.

5. MOISTURE BARRIER: ALL SURFACES EXPOSED TO WEATHER SHALL HAVE A WEATHER RESISTANT BARRIER TO PROTECT THE INTERIOR WALL AND CEILING COVERINGS...

6. Z-PAR: ALL HORIZONTAL JOINTS IN STAIRS SHALL BE PROTECTED BY GALVANIZED 1/2" Z-PAR FLASHING...

7. ROOF OVERHANG: ALL OVERHANGS SHALL BE FINISHED WITH A WEATHER RESISTANT BARRIER TO PROTECT THE INTERIOR WALL AND CEILING COVERINGS...

8. ELECTRICAL MATERIALS: ALL ELECTRICAL WIRING SHALL BE IN CONDUIT SYSTEMS AND SHALL MEET OR EXCEED THE REQUIREMENTS OF THE (CEC) CALIFORNIA ELECTRICAL CODE.

9. ROOF OVERHANG: ALL OVERHANGS SHALL BE FINISHED WITH A WEATHER RESISTANT BARRIER TO PROTECT THE INTERIOR WALL AND CEILING COVERINGS...

10. CONDUIT: ALL CONDUIT SHALL BE CONFORMS TO THE REQUIREMENTS OF THE (CEC) CALIFORNIA ELECTRICAL CODE.

11. CONDUIT: ALL CONDUIT SHALL BE CONFORMS TO THE REQUIREMENTS OF THE (CEC) CALIFORNIA ELECTRICAL CODE.

12. CONDUIT: ALL CONDUIT SHALL BE CONFORMS TO THE REQUIREMENTS OF THE (CEC) CALIFORNIA ELECTRICAL CODE.

13. CONDUIT: ALL CONDUIT SHALL BE CONFORMS TO THE REQUIREMENTS OF THE (CEC) CALIFORNIA ELECTRICAL CODE.

VARIABLE SPECIFICATIONS

1. WINDOW: HORIZONTAL SLUNG, BOX VENUED, CLEAR ANODIZED ALUMINUM FRAME, SIZED PER FLOOR PLAN.

2. FLOOR COVERING AND BASE: (MEETING CLASS I FLAMMABILITY) FLOOR COVERING: 24 OZ. CARPET

3. INTERIOR WALLS: (SHORE DEVELOPMENT MAX. 450) VAN COATED PAPERED CLASS II PLANK STREAK EATING, 8 OZ PER SQUARE YARD.

4. CEILING: (SHORE DEVELOPMENT MAX. 450) 5/8" x 2" x 4" VINYL FACED INTERIOR PAPERED WHITE (PLANK SPREAD CLASS I, 0-25)

5. MARKERBOARDS: 8' x 4' TR-100 PAPER OR EQUIV. (PLANK SPREAD CLASS I, 0-25)

6. INSULATION: R-19 FLOORS AND WALLS, R-19 CEILING. OTHER R-19 FLOORS, R-19 CEILING.

7. FIRE EXTINGUISHER: PREPARED TYPE, 2A/B/C, UL RATED WITH CHARGE P.W. AND QUICK RELEASE MOUNTING BRACKET.

8. SOFFIT DEPTH: EXPOSED SOFFIT. NOMINAL DEPTH SOFFIT. OTHER (SPECIFY)

9. ROOF OVERHANG: FRONT 5', REAR 2'. FRONT 5', REAR 5'. OTHER (SPECIFY)

10. CASEWORK: NONE. OTHER (SPECIFY)

11. WINDOW: HORIZONTAL SLUNG, BOX VENUED, CLEAR ANODIZED ALUMINUM FRAME, SIZED PER FLOOR PLAN.

12. FLOOR COVERING AND BASE: (MEETING CLASS I FLAMMABILITY) FLOOR COVERING: 24 OZ. CARPET

13. INTERIOR WALLS: (SHORE DEVELOPMENT MAX. 450) VAN COATED PAPERED CLASS II PLANK STREAK EATING, 8 OZ PER SQUARE YARD.

14. CEILING: (SHORE DEVELOPMENT MAX. 450) 5/8" x 2" x 4" VINYL FACED INTERIOR PAPERED WHITE (PLANK SPREAD CLASS I, 0-25)

15. MARKERBOARDS: 8' x 4' TR-100 PAPER OR EQUIV. (PLANK SPREAD CLASS I, 0-25)

16. INSULATION: R-19 FLOORS AND WALLS, R-19 CEILING. OTHER R-19 FLOORS, R-19 CEILING.

GENERAL NOTES

ALL JOINTS SHALL BE SEALED WITH ARCHITECTURAL GROUT CALLING OUT TO ARCHITECTURAL DRAWINGS.

WHEN MATERIALS ARE INSTALLED WITH CONCEALED JOINTS, THE JOINTS SHALL BE SEALED WITH ARCHITECTURAL GROUT CALLING OUT TO ARCHITECTURAL DRAWINGS.

WHEN MATERIALS ARE INSTALLED WITH CONCEALED JOINTS, THE JOINTS SHALL BE SEALED WITH ARCHITECTURAL GROUT CALLING OUT TO ARCHITECTURAL DRAWINGS.

WHEN MATERIALS ARE INSTALLED WITH CONCEALED JOINTS, THE JOINTS SHALL BE SEALED WITH ARCHITECTURAL GROUT CALLING OUT TO ARCHITECTURAL DRAWINGS.

WHEN MATERIALS ARE INSTALLED WITH CONCEALED JOINTS, THE JOINTS SHALL BE SEALED WITH ARCHITECTURAL GROUT CALLING OUT TO ARCHITECTURAL DRAWINGS.

WHEN MATERIALS ARE INSTALLED WITH CONCEALED JOINTS, THE JOINTS SHALL BE SEALED WITH ARCHITECTURAL GROUT CALLING OUT TO ARCHITECTURAL DRAWINGS.

WHEN MATERIALS ARE INSTALLED WITH CONCEALED JOINTS, THE JOINTS SHALL BE SEALED WITH ARCHITECTURAL GROUT CALLING OUT TO ARCHITECTURAL DRAWINGS.

WHEN MATERIALS ARE INSTALLED WITH CONCEALED JOINTS, THE JOINTS SHALL BE SEALED WITH ARCHITECTURAL GROUT CALLING OUT TO ARCHITECTURAL DRAWINGS.

WHEN MATERIALS ARE INSTALLED WITH CONCEALED JOINTS, THE JOINTS SHALL BE SEALED WITH ARCHITECTURAL GROUT CALLING OUT TO ARCHITECTURAL DRAWINGS.

WHEN MATERIALS ARE INSTALLED WITH CONCEALED JOINTS, THE JOINTS SHALL BE SEALED WITH ARCHITECTURAL GROUT CALLING OUT TO ARCHITECTURAL DRAWINGS.

WHEN MATERIALS ARE INSTALLED WITH CONCEALED JOINTS, THE JOINTS SHALL BE SEALED WITH ARCHITECTURAL GROUT CALLING OUT TO ARCHITECTURAL DRAWINGS.

WHEN MATERIALS ARE INSTALLED WITH CONCEALED JOINTS, THE JOINTS SHALL BE SEALED WITH ARCHITECTURAL GROUT CALLING OUT TO ARCHITECTURAL DRAWINGS.

WHEN MATERIALS ARE INSTALLED WITH CONCEALED JOINTS, THE JOINTS SHALL BE SEALED WITH ARCHITECTURAL GROUT CALLING OUT TO ARCHITECTURAL DRAWINGS.

WHEN MATERIALS ARE INSTALLED WITH CONCEALED JOINTS, THE JOINTS SHALL BE SEALED WITH ARCHITECTURAL GROUT CALLING OUT TO ARCHITECTURAL DRAWINGS.


WHEN MATERIALS ARE INSTALLED WITH CONCEALED JOINTS, THE JOINTS SHALL BE SEALED WITH ARCHITECTURAL GROUT CALLING OUT TO ARCHITECTURAL DRAWINGS.

WHEN MATERIALS ARE INSTALLED WITH CONCEALED JOINTS, THE JOINTS SHALL BE SEALED WITH ARCHITECTURAL GROUT CALLING OUT TO ARCHITECTURAL DRAWINGS.

PACESTER INDUSTRIES, INC. 24x40 RELOCATABLE BUILDING

P.O. BOX 1191, MODESTO, CA 95339 (209) 521-1800

NORMAN A. GEIGER, ARCHITECTURAL SERVICES, 96841 Sacramento, CA 95822-2463



SHEET CONTENTS: GENERAL SPECIFICATIONS, VARIABLE SPECIFICATIONS, GENERAL NOTES


Table with columns: DATE, REV. #, REV. DESCRIPTION, DRAWING SCALE, PROJECT NUMBER, SHEET

A1

APPROVALS

Approval signatures and dates for PC 330, dated NOV 20 1997.

THESE DRAWINGS AND/OR CALCULATIONS FOR THE ITEMS LISTED BELOW HAVE BEEN PREPARED BY OTHER DESIGN PROFESSIONALS WHO ARE LICENSED AND EXAMINED BY ME AND HAVE BEEN FOUND TO MEET THE APPROPRIATE REQUIREMENTS OF TITLE 24, CALIFORNIA CODE OF REGULATIONS AND THE PROJECT SPECIFICATIONS PREPARED BY ME.



EXP. DATE: 11/20/98