

THESE DRAWINGS AND SPECIFICATIONS ARE PRELIMINARY AND SUBJECT TO CHANGE WITHOUT NOTICE. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS FROM THE APPROPRIATE AGENCIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS FROM THE APPROPRIATE AGENCIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS FROM THE APPROPRIATE AGENCIES.

ROOM OR SPACE	FLOOR	BASE	WALLS	CEILING	REMARKS
1 GENERAL OFFICE	1	A	B	C	
2 HEALTH	1	A	B	C	
3 WORK ROOM	1	A	B	C	
4 TOILET	1	A	B	C	
5 HALL	1	A	B	C	
6 CONFERENCE	1	A	B	C	
7 PRINCIPAL'S OFFICE	1	A	B	C	
8 STORAGE	1	A	B	C	
9 CLOSET	1	A	B	C	

NO	SIZE	DOOR	FRM	REMARKS
1	5'-0" x 7'-0"	1/2 HD A W/D		DOOR W/ 5 LB PRESSURE
2	5'-0" x 7'-0"	1/2 HD A W/D		DOOR W/ 5 LB PRESSURE
3	5'-0" x 7'-0"	1/2 HD A W/D		DOOR W/ 5 LB PRESSURE
4	5'-0" x 7'-0"	1/2 HD A W/D		DOOR W/ 5 LB PRESSURE
5	5'-0" x 7'-0"	1/2 HD A W/D		DOOR W/ 5 LB PRESSURE
6	5'-0" x 7'-0"	1/2 HD A W/D		DOOR W/ 5 LB PRESSURE
7	5'-0" x 7'-0"	1/2 HD A W/D		DOOR W/ 5 LB PRESSURE
8	5'-0" x 7'-0"	1/2 HD A W/D		DOOR W/ 5 LB PRESSURE
9	5'-0" x 7'-0"	1/2 HD A W/D		DOOR W/ 5 LB PRESSURE
10	5'-0" x 7'-0"	1/2 HD A W/D		DOOR W/ 5 LB PRESSURE

NOTES:  
 1. ALL LIGHT FIXTURES SHALL BE 5000K CRI 90+ LED LIGHTING.  
 2. ALL LIGHT FIXTURES SHALL BE 5000K CRI 90+ LED LIGHTING.  
 3. ALL LIGHT FIXTURES SHALL BE 5000K CRI 90+ LED LIGHTING.  
 4. ALL LIGHT FIXTURES SHALL BE 5000K CRI 90+ LED LIGHTING.  
 5. ALL LIGHT FIXTURES SHALL BE 5000K CRI 90+ LED LIGHTING.

1. Hanger wires shall be provided for all main runners and cross runners within 8" of ceiling perimeter.
2. Hanger wires that are more than 1 in 6 out of plumb shall have counterbalanced wires.
3. Ceiling grid may be attached to 2 adjacent walls; the ceiling grid shall be at least 1 inch free of other walls.
4. Cross runners over 12' long and all main runners not supported by walls shall be supported by the ceiling grid.
5. A set of 4 gphw wires shall be provided for each 144 sq. ft. of ceiling area. First set of gphw wires shall be 6'-0" from any wall for schools. Wires shall be cast without casting ceiling to lift.
6. Hanger wires must be fastened with not less than 3 light 3/8" diameter bolts for 12' ga or 3/4" diameter bolts for 18' ga.
7. All ceiling wires and unbraced ducts, pipes etc. must be supported.
8. All light fixtures shall be attached to the ceiling grid to resist a horizontal force equal to the weight of the fixtures.
9. Plumb or recessed light fixtures and air terminals or services weighing less than 50 pounds may be supported on the ceiling grid.
10. A material other than that listed on the plans and specifications is proposed, it must be approved by the Architect or Engineer and the State Architect prior to installation.

