


**B TYPICAL TRANSVERSE FRAME**  
S4 3/8"=1'-0"




**A TYPICAL LONGITUDINAL FRAME**  
S4 3/8"=1'-0"


- KEY NOTES -**
- HSS 4x4x5/16" COLUMN
  - FLOOR BEAM PER SCHEDULE BELOW
  - LONGITUDINAL ROOF CHANNEL PER 10/S3.1
  - 12 GA. TRANSVERSE ROOF CHANNEL 14" MIN 18" MAX PER 11/S3.1
  - 6" Ø MAX OPENING IN WEB OF ROOF BEAM WITHOUT WEB REINFORCEMENT. MINIMUM SPACING OF HOLES @ 48" O.C. HOLES MAY OCCUR @ ANY LOCATION ALONG LENGTH OF ROOF BEAM EXCEPT AS NOTED OTHERWISE ON FRAMING ELEVATION. NOTE: IF HOLE IS 3" OR LESS THEY MAY BE SPACED AT 24" O.C. MINIMUM
  - 4" Ø MAX OPENING IN WEB OF FLOOR BEAM WITHOUT WEB REINFORCEMENT. MINIMUM SPACING OF HOLES @ 48" O.C. HOLES MAY OCCUR @ ANY LOCATION ALONG LENGTH OF FLOOR BEAM WITH DIRECT FOUNDATION SUPPORT BELOW. OPENINGS ARE NOT ALLOWED WHERE BEAMS ARE SPANNING BETWEEN FOUNDATIONS OR ACROSS VENT OPENINGS.  
NOTE: IF HOLE IS 2" OR LESS THEY MAY BE SPACED AT 24" MINIMUM
  - 12 GA OUTRIGGER CHANNEL AT ELEVATION REFER TO DETAIL 1/S4A
  - OPENING FOR HVAC UNIT

**- FLOOR BEAM SCHEDULE -**


SUBFLOOR TYPE	FLOOR BEAM SIZE	ALTERNATES
VIROC OR PLYWOOD	C7x9.8	C9x13.4, C10x15.3
CONCRETE	C9x13.4	C10x15.3




**5 OPENING @ ROOF BEAMS**  
S4A 1 1/2"=1'-0"





**3 OVERHANG CORNER DETAIL**  
S4A N.T.S.





**6 OPENING @ FLOOR BEAM**  
S4A 1 1/2"=1'-0"



**7 TYPICAL BEAM SPLICE**  
S4A N.T.S.





**4 OPENING @ TRANSVERSE ROOF BEAMS**  
S4A 1 1/2"=1'-0"



**2 TYPICAL CORNER TO BEAM DETAIL**  
S4A 1 1/2"=1'-0"

THE WELDING PROCEDURE QUALIFICATION TEST RECORD AND WELDING PROCEDURE SPECIFICATION FOR THIS WELD SHALL BE PREPARED IN ACCORDANCE WITH AWS D.1-06 AND SUBMITTED TO THE STRUCTURAL ENGINEER FOR REVIEW AND SUBMITTAL TO THE D.S.A. TYPICAL DETAILS 1/S4A, 2/S4A AND 7/S4A. ALL WELDS USED IN PRIMARY MEMBERS AND CONNECTIONS IN THE LATERAL FORCE-RESISTING SYSTEMS SHALL BE MADE WITH A FILLER METAL THAT HAS A MINIMUM CHARPY V-NOTCH TOUGHNESS OF 20 FT.-LBS AT ZERO DEGREES F, AS DETERMINED BY AWS CLASSIFICATION.



**1 TYPICAL ROOF CHANNEL TO HSS DETAIL**  
S4A 1 1/2"=1'-0"

**REVISIONS**

NO.	DATE	DESCRIPTION

DATE: 02/04/08  
SCALE: NOTED  
DRAWN BY: RL  
SERIAL NO.:

CUSTOMER:  
2:12 PITCHED ROOF 24' x 40' THRU 120' x 40' RELOCATABLE BUILDINGS  
TYPICAL FRAME ELEVATIONS

**AMS**  
American Modular Systems Inc.  
787 Sprackels Ave. Manteca, CA 95336  
(209)825-1921 Fax (209)825-7018  
americanmodular.com

APPROVALS:  
THESE DRAWINGS ARE PRELIMINARY AND NOT FOR CONSTRUCTION UNLESS STAMPED & SIGNED BY THE ENGINEER OF RECORD.

IDENTIFICATION STAMP  
NO. 02-112985  
DATE: SEP 27 2009

IDENTIFICATION STAMP  
DIV. OF THE STATE ARCHITECT  
OFFICE OF REGULATION SERVICES  
PC 02-109695  
DATE: 3/3/2009  
**S4**

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF AMERICAN MODULAR SYSTEMS AND ARE NOT TO BE REPRODUCED, CHANGED OR COPIED IN ANY FORM OR MANNER, NOR ARE THEY TO BE ASSIGNED TO ANY THIRD PARTY WITHOUT THE WRITTEN AUTHORIZATION OF AMERICAN MODULAR SYSTEMS.