

FLOOR PLAN


SCALE 1/4"=1'-0"

KEY NOTES

- 1 ROOF OVERHANG
- 2 HVAC UNIT - [HV]
- 3 2- 8'X4' MARKER BOARDS (SEE SPECS FOR TYPE)
- 4 FINISH FLOORING (SEE FINISH SCHED.) AS O
- 5 TYPICAL INTERIOR FINISH (SEE FINISH SCHEDULE) AS O
- 6 FIRE EXTINGUISHER - 5 LBS. DRY CHEMICAL WITH 2A-10BC U.L. RATINGS ON WALL MTD. BRACKET. HANDLE AT +48" A.F.F.
- 7 MODLINE (M) TYPICAL
- 8 LINE OF RAMP/LANDING (SEE SH1 R10/R20.0)

NOTES

1. METAL TAG ON ALL MODULES, MECHANICALLY ATTACHED TO REAR EXTERIOR OF BUILDING SHOWN D.S.A. APPLICATION NUMBER, MANUFACTURER'S NAME AND SERIAL NUMBER, ROOF AND FLOOR DESIGN LIVE LOAD, AND DESIGN WIND LOAD.
2. INSULATION MATERIALS INSTALLED WITHIN FLOOR, CEILING ASSEMBLIES, ROOF-CEILING ASSEMBLIES, WALLS, CRAWL SPACES, PRATTICES SHALL HAVE A FLAME SPREAD RATING NOT TO EXCEED 25 AND A SMOKE DENSITY NOT TO EXCEED 450. EXCEPTIONS:  
 1. FOAM PLASTIC INSULATION SHALL COMPLY WITH SEC. 2602.  
 2. WHEN MATERIALS ARE INSTALLED IN CONCEALED SPACES OF TYPES I, II, IV, AND V CONSTRUCTION, THE FLAME SPREAD AND SMOKE DEVELOPED LIMITATIONS DO NOT APPLY TO FACINGS IF THE FACING IS INSTALLED IN SUBSTANTIAL CONTACT WITH THE UNEXPOSED SURFACE OF THE CEILING, FLOOR OR WALL FINISH. (SEC. 707.3 CBC)



REVISIONS	ELECTRICAL	MECHANICAL	STRUCTURAL	ARCHITECT	DIVISION OF THE STATE ARCHITECT

--	--	--	--

**MODTECH INC.**  
 2090 LARRETT AVE  
 FERRIS, CA 94512  
 PH. (909) 945-4014  
 FX. (909) 945-0427

**WORLDWIDE INC.**

4012-085 **STRP-40**

	JOB NO. DATE CHECKED BY DATE
3060 2928	<b>FLOOR PLAN A1.0</b>