



- ### KEY NOTES
- 1 TS 2" x 2" x 14ga
 - 2 TS 1 1/2" x 1 1/2" x 14ga (Fy = 39 KSI)
 - 3 TS 1 1/4" x 1 1/4" x 14ga (Fy = 39 KSI)
 - 4 TS 1" x 1" x 15ga WHEELCHAIR GUIDE
 - 5 2 x 6 PT SILL PLATE
 - 6 2 x 2 NAILEP W/16d @ 12" OC
 - 7 2 x RW HEADER BY DISTRICT.
 - 8 6" x 10ga CONTINUOUS PLATE W/#14 x 2" TEK SCREWS @ 9" OC INTO WOOD OR FOUNDATION BLOCKS OR #14 x 2" TEK SCREWS INTO METAL @ 9" OC
 - 11 2" x 4" x 12ga BASE PLATE W/2-1/4" x 1" LAGS
 - 12 6" x 10" x 12ga BASE PLATE @ RAMP TOE.
 - 14 LOWER LANDING BY DISTRICT
 - 15 SKIRTING: PLYWOOD TO MATCH BUILDING SIDING. BLOCK ALL EDGES. ATTACH W/8d @ 6" OC EDGES AND 12" OC FIELD. AT EDGE CONNECTION TO T.S. USE #14 x 2" TEK SCREWS @ 6" OC
 - 16 12ga METAL DECK: NON-SLIP SURFACE. DESIGN COEFFICIENT OF FRICTION GREATER THAN 6%. MAINTAINABLE FOR 1 YR. EXISTING BUILDING.
 - 18 CAULKING
 - 20 28 ga FLASHING
 - 23 3/8" dia x 2" LONG MB W/NIIT & WASHERS
 - 26 PAVE BY DISTRICT.
 - 27 RAMP BY MODTECH
 - 28 FLUSH TRANSITION
 - 29 3" MINIMUM BUILDING SEPERATION
 - 30 PROVIDE DIVERSION FOR WATER FROM DOWNSPOUT FOR THIS CONDITION. BY DISTRICT
 - 32 FOR LANDING DETAILS AND RAMP ATTACHMENT SEE 12/R1.0
 - 33 FASTEN POSTS W/ 3/8" @ THRU BOLT. TYPICAL
 - 34 2" WARNING STRIPES MAX 1" FROM EVERY STAIR NOSING. USE CONTRASTING COLOR.
 - 36 TS 2 1/2" x 1 1/2" x 8ga ASTM A500 GRADE A

REVISIONS

1		
2		
3		
4		
5		

Electrical Engineer's Seal
 Mechanical Engineer's Seal
 Structural Engineer's Seal

Architect's Seal
 IDENTIFICATION STAMP
 DIV. OF THE STATE ARCHITECT
 OFFICE OF REGULATION SERVICES
 PC 284
 AC 11/11/98
 DATE MAY 6 1998
REVISED

MODTECH INC.
 2830 BARRETT AVENUE
 PERRIS, CALIF. 92572
 PH (909) 943-4014
 FAX (909) 940-0427

Job Number: PC 284
 © MODTECH, INC. 1997
 Job Number: PC 284
 JOB# 2724 # 2818-C
 ANAHEIM UHSD.
 (CLASS LEASING)

4012-081
 CLLS.036
 MODTECH Index No.
R2.0

RAMP/STAIR DETAILS