



- GENERAL NOTES**
- DESIGN SOIL PRESSURE - 1500 P.S.F.
 - LAG BOLTS TO BE INSERTED INTO 1/4" DIA HOLES PRE-DRILLED IN WOOD FOOTING.
 - THE THREADED PORTION OF THE LAG BOLT SHALL BE INSERTED IN ITS LEAD HOLE BY TURNING WITH A WRENCH, NOT BY DRIVING WITH A HAMMER.
 - ALL WOOD FOOTINGS SHALL BE FOUNDATION GRADE REDWOOD OR DOUGLAS FIR TREATED AS PER REQUIRED IN TITLE 21.
 - 4x12 OR 4x8 PLANKS MAY BE REPLACED BY 2x12 OR 2x8 TO PROVIDE BETTER GRADE ADJUSTMENT.
 - BOTTOM PLANKS SHALL ALWAYS BE ALWAYS 4x12 OR 4x8 SUBGRADE FOR EACH FOOTING TO BE LEVELED AROUND TO FOOTING INSTALLATION.

NO.	REVISIONS

APPROVED BY	STATE FIRE MARSHALL
APPROVED BY	STRUCTURAL ENGINEER
APPROVED BY	ARCHITECT
APPROVED BY	

OFFICE OF ARCHITECTURE & CONSTRUCTION
BAKERSFIELD, CALIFORNIA

**EISLER ELEM. SCHOOL
BAKERSFIELD CITY SD**

RELOCATABLE BUILDING
FOUNDATION PLAN & DETAILS

DRAWN BY: [Signature]
CHECKED BY: [Signature]
DATE: 12-18-57
SCALE: A5 NOTES
APPROVED BY: [Signature]
W. O. NO. 3022
COUNT NO. 8022
DWG. NO. S-1

2200